



Figure similar

MLFB-Ordering data 1FK2206-2AF10-0SA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Basic motor data		Mechanical data	
Motor type	Permanent-magnet synchronous motor, Natural cooling, IP64	Design acc. to Code I	IM B5 (IM V1, IM V3)
Motor type	Compact	Vibration severity grade	Grade A
Static torque	6.50 Nm	Shaft height	63
Static current	5.0 A	Flange size (AB)	125 mm
Maximum torque	18.00 Nm	Centering ring (N)	110 mm
Maximum current	17.8 A	Hole circle (M)	130 mm
Maximum speed	6000 rpm	Screw-on hole (S)	9.0 mm
Rotor moment of inertia	9.400 kgcm²	Overall length (LB)	205 mm
Weight	7.9 kg	Diameter of shaft (D)	24 mm
Rated data		Length of shaft (E)	50 mm
		Length of flange diagonal (P)	158 mm
		Shaft extension	Plain shaft

SINAMICS S210, 3AC 400V

Rated speed	3000 rpm
Rated torque	5.40 Nm
Rated current	4.4 A
Rated power	1.71 kW

Encoder system	
Encoder system	Encoder AS22DQC: Absolute encoder single turn 22 bit

Motor connection	
Connection type	OCC for S210
Connector size	M23




Figure similar

1FK2206-2AF10-0SA0

<sup>1)</sup> Up to three consecutive emergency stops and up to 25% of all emergency stops as a Wmax high energy stop possible.

<sup>2)</sup> Typical value for 20°C ambient temperature. At -15°C the break-induced currents can be increased by up to 30%.