

DATASHEET - K20X15/40-A



Busbar terminal f. CU20x5(x10, x15)

Part no. K20X15/40-A
Catalog No. 012783

EL-Nummer 0002459132
(Norway)



Delivery program

Product range			Ci insulated enclosures
Basic function			Prepared enclosures
Product function			Modular busbar system
Accessories			Terminal
Single unit/Complete unit			Modular system
Function			For fuse enclosures and busbar fuse enclosures as well as SE-RS-I43 busbar assemblies
For use with			CU20X5 CU20X10 CU20X15
Notes Terminal capacity for flat strip: from 3 x 9 x 0.8 mm Up to 10 x 16 x 0.8 mm Ø 4 - 10 mm ² (solid)			

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])			
Busbar thickness		mm	5 - 10
Busbar width		mm	20 - 20
Suitable for			Flat rail
Width clamp		mm	32
Max. conductor cross section		mm ²	124
Max. rated operation current I _e		A	400
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			No
Suitable for strip conductor connection			Yes

Additional product information (links)

Manufacturer's Declaration CI-RoHS	ftp://ftp.moeller.net/DOCUMENTATION/PDF/2013-01-31_Ci_RoHS.pdf
Declaration of conformity	ftp://ftp.moeller.net/DOCUMENTATION/PDF/ci_ce.pdf