

SIPLUS S7-300 CPU 315F-2DP -25 ... +60 DEGREES C
WITH CONFORMAL COATING BASED ON 6ES7315-6FF04
-0AB0 . FAILSAFE CPU WITH MPI INTERFACE
INTEGRATED 24V DC POWER SUPPLY,
384 KB WORKING MEMORY, 40MM WIDE,
2. INTERFACE DP-MASTER/SLAVE MICRO MEMORY
CARD REQUIRED

Certificates/approvals:

General Product Approval

[FM](#)



KEMA

[TÜV](#)



UL

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/6AG1315-6FF04-2AB0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=6AG1315-6FF04-2AB0

last change: