TNC Reverse Polarity Crimp Plug

RT1121A1-NT-3G-LMR200-50

EAN: 5704717008193

Egnede kabler:
LMR200



RPTNC male crimp for LMR200

7479RPLMR

REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE



RECOMMENDED
CABLE STRIPPING DIM'S
(建議剝線尺寸)







NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS
2. NICKEL PL. 100 MIN. THICK OVER COPPER PL. 50 MIN. THICK
3. PHOSPHOR BRONZE
4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
5. TEFLON

1. CRIMPED FERRULE HEX CRIMP SIZE .213"
2. CRIMPED CONTACT PIN HEX CRIMP SIZE .068"

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
10	FERRULE	COPPER	NOTE 2	1	FR-533-648-127C
9	CONTACT PIN	NOTE 3	NOTE 4	1	900-6000-8-1.2
8	SHELL	NOTE 1	NOTE 2	1	71628-1000-1
7	GASKET	RUBBER	RED	1	GS-80-105-15
6	RETAINER RING	NOTE 1	NOTE 2	1	900-1000-5
5	RING	DELRIN	NATURAL	1	71628-1000-6
4	WASHER	NOTE 1	NOTE 2	1	WS-90-128-08
3	BARREL	NOTE 1	NOTE 2	1	71628RP-1000-3-08
2	INSULATOR	NOTE 5	NATURAL	1	71628RP-1121A2-2-50T
1	BODY	NOTE 1	NOTE 2	1	71628RP-1000-1

DIMENSIONS ARE IN MILLIMETERS

UNLESS OTHERWISE SPECIFIED TOLERANCES
0.5-6 = ±0.2
6-30 = ±0.4
30-120 = ±0.6
120-315 = ±1
315-1000 = ±1.6
1000-2000 = ±2.4

SCALE 3/1 ISSUE A

PART NO.

APPROVED DATE 10-14-'11

CHECKED DATE 10-14-'11

DRAWN DATE 10-14-'11

TITLE TNC REVERSE POLARITY CRIMP PLUG (FOR LMR-200 CABLE)

DRAWING NO. 71628RP-1121A2-08-50

FILE NO. R:\D\G\DWG\71628\RP\1121A2\08\50

DMTonline ApS • Kjeldgaardsvej 1 • DK-9300 Sæby • Tlf. +45 98461333 • info@dmtonline.dk • www.dmtonline.dk