



FlexBlend heading the way to efficient and flexible furnished offices areas

FlexBlend, Surface Mounted

Philips FlexBlend is an attractive family of surface mounted and suspended luminaires, next to Flexblend recessed. The luminaire range is enabling building owners to advance their lighting operations, by offering office-compliant lighting with a return on investment of less than 3 to 4 years. FlexBlend provides the required flexibility through the adaptability in design. This gives the possibility to install the luminaires easily in the field, at any moment. Even when today's luminaire is suspended, tomorrow this can be adapted to a surface mounted installation at the venue. And the other way around. The surface mounted and suspended luminaire range fit to many different office spaces like open plan office, corridors, reception or meeting rooms. FlexBlend is offered in both lines and as standalone, using the same lighting module. This gives the option to the users to use FlexBlend as standalone now, and tomorrow, as line. The controller is integrated in the luminaire. As technology is changing fast, the ideal lighting solution is also expected to be ready to incorporate innovations that can help optimize operations further. For this reason, FlexBlend holds all connectivity and future ready options available. As System Ready luminaire it can be paired with lighting management systems such as the Philips SpaceWise, and to software-based lighting systems as Interact Office wired (PoE) and Interact Office wireless and/or existing and upcoming sensor innovations. The luminaire range is therefore future ready and can be delivered without any system component, and in a next phase, in the field to be upgraded. An attractive opportunity for new installations and renovations.

FlexBlend, Surface Mounted

Benefits

- Return of investment less than 3 years
- A flexible office, with application flexibility to the choice of luminaires to fit many office areas
- Future ready: scalable and ready to be connected to controls and lighting systems

Features

- Fully office compliant (UGR <19, L65 < 3000cd/sm), light level according to office applications requirements
- Homogenous and uniform light effect
- Various mounting options, dimensional variety and local options
- Integrated sensors
- Ready to be connected to software based lighting systems such as Interact Office

Application

- Offices
- Education
- Healthcare

Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress & as such we strongly recommend that The environment in which The luminaire is to be installed is suitably checked
- If The above advice is not taken and The luminaires are subject to water ingress, Philips / Signify cannot guarantee safe failure & product warranty will become void

Versions



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE



FLEXBLEND STAND-ALONE

FlexBlend, Surface Mounted

Versions



FLEXBLEND STAND-ALONE

Product details


FlexBlend Surface Mounted
SM340C WH



FlexBlend Surface Mounted
SM340C WH



FlexBlend Suspended SP340P WH



FlexBlend Surface Mounted
SM340C brackets



FlexBlend Surface Mounted
SM340C SI




FlexBlend, Surface Mounted

Product details

FlexBlend Surface Mounted
SM340C SI



FlexBlend Suspended SP340P SI



FlexBlend Surface Mounted
SM340C PCS BK



FlexBlend Surface Mounted
SM340C BK



FlexBlend Surface Mounted
SM340C BK



FlexBlend Surface Mounted
SM340C BK



FlexBlend Surface Mounted
SM340C MLO BK



FlexBlend Surface Mounted
SM340C BK



FlexBlend Suspended SP340P BK



FlexBlend, Surface Mounted

Product details



FlexBlend Surface Mounted
SM340C O BK




FlexBlend Suspended SP340P WH



FlexBlend Surface Mounted
SM340C WH




FlexBlend Surface Mounted
SM340C MLO WH



FlexBlend Surface Mounted
SM340C O SI



FlexBlend Surface Mounted
SM340C




FlexBlend Surface Mounted
SM340C O SI

Accessories


FLEXBLEND S&S ACCESSORIES

Ordercode 910925867343



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867344




FLEXBLEND S&S ACCESSORIES

Ordercode 910925867345




FLEXBLEND S&S ACCESSORIES

Ordercode 910925867346



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867347



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867348




FLEXBLEND S&S ACCESSORIES

Ordercode 910925867349,
910925867351



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867437



Accessories

FLEXBLEND S&S ACCESSORIES

Ordercode 910925867438



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867439



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867440,
910925867441



FLEXBLEND S&S ACCESSORIES

Ordercode 910925867442,
910925867444



FlexBlend, Surface Mounted

Application Conditions

Ambient temperature range	+10 to +40 °C
Maximum dim level	1%
Suitable for random switching	Yes (relates to presence/ movement detection and daylight harvesting)

Approval and Application

Mech. impact protection code	IK02
Ingress protection code	IP20

Operating and Electrical

Input Voltage	220 to 240 V
---------------	--------------

General Information

Beam angle of light source	120 °
CE mark	CE mark
Protection class IEC	Safety class I
Driver included	Yes
ENEC mark	ENEC mark
Flammability mark	For mounting on normally flammable surfaces
Light source replaceable	Yes
Number of gear units	1 unit
Optic type	Wide beam
Service tag	Yes

Initial Performance (IEC Compliant)

Initial chromaticity	(0.43, 0.40) SDCM <3
Init. Color Rendering Index	>95
Luminous flux tolerance	+/-8%

Controls and Dimming

Order Code	Full Product Name	Dimmable
910925867099	SM340C 35S/940 PSD PCS L150 WH	Yes
910925867103	SM340C 35S/940 SRD PCS SWZU L150 WH	Wireless Dim
910925867125	SM340C 35S/930 SRD PCS SWZU L150 WH	Wireless Dim
910925867134	SM340C 36S/940 PSD PCS L120 WH	Yes
910925867135	SM340C 42S/940 PSD PCS L120 WH	Yes
910925867865	SM340C 28S/940 PSD PCS L120 WH	Yes
910925867868	SM340C 28S/930 PSD PCS L120 WH	Yes
910925867869	SM340C 36S/930 PSD PCS L120 WH	Yes
910925867878	SM340C 45S/940 PSD PCS L150 WH	Yes
910925867879	SM340C 52S/940 PSD PCS L150 WH	Yes
910925867882	SM340C 35S/930 PSD PCS L150 WH	Yes
910925867883	SM340C 45S/930 PSD PCS L150 WH	Yes
910925867893	SM340C 45S/940 SRD PCS SWZU L150 WH	Wireless Dim
910925867894	SM340C 52S/940 SRD PCS SWZU L150 WH	Wireless Dim
910925867897	SM340C 35S/940 PSD-T PCS ACL L150 WH	Yes
910925867898	SM340C 45S/940 PSD-T PCS ACL L150 WH	Yes
910925867902	SM341C 26S/940 PSD PCS L150 WH	Yes
910925867903	SM341C 35S/940 PSD PCS L150 WH	Yes
910925867910	SM341C 26S/940 SRD PCS SWZU L150 WH	Wireless Dim
910925867911	SM341C 35S/940 SRD PCS SWZU L150 WH	Wireless Dim
910925867914	SM341C 26S/940 PSD-T PCS ACL L150 WH	Yes
910925867915	SM341C 35S/940 PSD-T PCS ACL L150 WH	Yes
910925867101	SM340C 35S/940 PSD PCS L150 SI	Yes
910925867873	SM340C 28S/940 PSD PCS L120 SI	Yes
910925867874	SM340C 36S/940 PSD PCS L120 SI	Yes
910925867887	SM340C 45S/940 PSD PCS L150 SI	Yes
910925867888	SM340C 52S/940 PSD PCS L150 SI	Yes
910925867906	SM341C 26S/940 PSD PCS L150 SI	Yes
910925867907	SM341C 35S/940 PSD PCS L150 SI	Yes
910925867102	SM340C 35S/940 PSD PCS L150 BK	Yes
910925867108	SM340C 35S/940 PSD MLO L150 WH	Yes
910925867111	SM340C 35S/940 SRD MLO SWZU L150 WH	Wireless Dim
910925867136	SM340C 36S/940 PSD MLO L120 WH	Yes
910925867137	SM340C 40S/940 PSD MLO L120 WH	Yes
910925867262	SM341C 35S/940 PSD MLO L150 WH	Yes
910925867866	SM340C 28S/940 PSD MLO L120 WH	Yes
910925867870	SM340C 28S/930 PSD MLO L120 WH	Yes
910925867871	SM340C 36S/930 PSD MLO L120 WH	Yes
910925867880	SM340C 45S/940 PSD MLO L150 WH	Yes
910925867881	SM340C 50S/940 PSD MLO L150 WH	Yes
910925867884	SM340C 35S/930 PSD MLO L150 WH	Yes
910925867885	SM340C 45S/930 PSD MLO L150 WH	Yes
910925867895	SM340C 45S/940 SRD MLO SWZU L150 WH	Wireless Dim
910925867896	SM340C 50S/940 SRD MLO SWZU L150 WH	Wireless Dim
910925867899	SM340C 35S/940 PSD-T MLO ACL L150 WH	Yes
910925867901	SM340C 45S/940 PSD-T MLO ACL L150 WH	Yes
910925867904	SM341C 26S/940 PSD MLO L150 WH	Yes
910925867912	SM341C 26S/940 SRD MLO SWZU L150 WH	Wireless Dim
910925867913	SM341C 35S/940 SRD MLO SWZU L150 WH	Wireless Dim
910925867916	SM341C 26S/940 PSD-T MLO ACL L150 WH	Yes
910925867917	SM341C 35S/940 PSD-T MLO ACL L150 WH	Yes

FlexBlend, Surface Mounted

Order Code	Full Product Name	Dimmable
910925867109	SM340C 35S/940 PSD MLO L150 SI	Yes
910925867875	SM340C 28S/940 PSD MLO L120 SI	Yes
910925867876	SM340C 36S/940 PSD MLO L120 SI	Yes
910925867889	SM340C 45S/940 PSD MLO L150 SI	Yes
910925867890	SM340C 50S/940 PSD MLO L150 SI	Yes
910925867908	SM341C 26S/940 PSD MLO L150 SI	Yes
910925867909	SM341C 35S/940 PSD MLO L150 SI	Yes
910925867110	SM340C 35S/940 PSD MLO L150 BK	Yes
910925867116	SM340C 35S/940 PSD O L150 WH	Yes
910925867867	SM340C 36S/940 PSD O L120 WH	Yes
910925867872	SM340C 36S/930 PSD O L120 WH	Yes
910925867886	SM340C 35S/930 PSD O L150 WH	Yes
910925867905	SM341C 26S/940 PSD O L150 WH	Yes
910925867877	SM340C 36S/940 PSD O L120 SI	Yes
910925867891	SM340C 35S/940 PSD O L150 SI	Yes
910925867892	SM340C 35S/940 PSD O L150 BK	Yes

General Information

Order Code	Full Product Name	Glow-wire test	Product Family Code
910925867099	SM340C 35S/940 PSD PCS L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867103	SM340C 35S/940 SRD PCS SWZU L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867125	SM340C 35S/930 SRD PCS SWZU L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867134	SM340C 36S/940 PSD PCS L120 WH	Temperature 850 °C, duration 30 s	SM340C
910925867135	SM340C 42S/940 PSD PCS L120 WH	Temperature 850 °C, duration 30 s	SM340C
910925867865	SM340C 28S/940 PSD PCS L120 WH	Temperature 850 °C, duration 30 s	SM340C
910925867868	SM340C 28S/930 PSD PCS L120 WH	Temperature 850 °C, duration 30 s	SM340C
910925867869	SM340C 36S/930 PSD PCS L120 WH	Temperature 850 °C, duration 30 s	SM340C
910925867878	SM340C 45S/940 PSD PCS L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867879	SM340C 52S/940 PSD PCS L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867882	SM340C 35S/930 PSD PCS L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867883	SM340C 45S/930 PSD PCS L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867893	SM340C 45S/940 SRD PCS SWZU L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867894	SM340C 52S/940 SRD PCS SWZU L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867897	SM340C 35S/940 PSD-T PCS ACL L150 WH	Temperature 850 °C, duration 30 s	SM340C

Order Code	Full Product Name	Glow-wire test	Product Family Code
910925867898	SM340C 45S/940 PSD-T PCS ACL L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867902	SM341C 26S/940 PSD PCS L150 WH	Temperature 850 °C, duration 30 s	SM341C
910925867903	SM341C 35S/940 PSD PCS L150 WH	Temperature 850 °C, duration 30 s	SM341C
910925867910	SM341C 26S/940 SRD PCS SWZU L150 WH	Temperature 850 °C, duration 30 s	SM341C
910925867911	SM341C 35S/940 SRD PCS SWZU L150 WH	Temperature 850 °C, duration 30 s	SM341C
910925867914	SM341C 26S/940 PSD-T PCS ACL L150 WH	Temperature 850 °C, duration 30 s	SM341C
910925867915	SM341C 35S/940 PSD-T PCS ACL L150 WH	Temperature 850 °C, duration 30 s	SM341C
910925867101	SM340C 35S/940 PSD PCS L150 SI	Temperature 850 °C, duration 30 s	SM340C
910925867873	SM340C 28S/940 PSD PCS L120 SI	Temperature 850 °C, duration 30 s	SM340C
910925867874	SM340C 36S/940 PSD PCS L120 SI	Temperature 850 °C, duration 30 s	SM340C
910925867887	SM340C 45S/940 PSD PCS L150 SI	Temperature 850 °C, duration 30 s	SM340C
910925867888	SM340C 52S/940 PSD PCS L150 SI	Temperature 850 °C, duration 30 s	SM340C
910925867906	SM341C 26S/940 PSD PCS L150 SI	Temperature 850 °C, duration 30 s	SM341C
910925867907	SM341C 35S/940 PSD PCS L150 SI	Temperature 850 °C, duration 30 s	SM341C
910925867102	SM340C 35S/940 PSD PCS L150 BK	Temperature 850 °C, duration 30 s	SM340C

FlexBlend, Surface Mounted

Order Code	Full Product Name	Glow-wire test	Product Family Code
910925867108	SM340C 35S/940 PSD MLO L150 WH	Temperature 650 °C, duration 30 s	SM340C
910925867111	SM340C 35S/940 SRD MLO SWZU L150 WH	Temperature 650 °C, duration 30 s	SM340C
910925867136	SM340C 36S/940 PSD MLO L120 WH	Temperature 650 °C, duration 30 s	SM340C
910925867137	SM340C 40S/940 PSD MLO L120 WH	Temperature 650 °C, duration 30 s	SM340C
910925867262	SM341C 35S/940 PSD MLO L150 WH	Temperature 650 °C, duration 30 s	SM341C
910925867866	SM340C 28S/940 PSD MLO L120 WH	Temperature 650 °C, duration 30 s	SM340C
910925867870	SM340C 28S/930 PSD MLO L120 WH	Temperature 650 °C, duration 30 s	SM340C
910925867871	SM340C 36S/930 PSD MLO L120 WH	Temperature 650 °C, duration 30 s	SM340C
910925867880	SM340C 45S/940 PSD MLO L150 WH	Temperature 650 °C, duration 30 s	SM340C
910925867881	SM340C 50S/940 PSD MLO L150 WH	Temperature 650 °C, duration 30 s	SM340C
910925867884	SM340C 35S/930 PSD MLO L150 WH	Temperature 650 °C, duration 30 s	SM340C
910925867885	SM340C 45S/930 PSD MLO L150 WH	Temperature 650 °C, duration 30 s	SM340C
910925867895	SM340C 45S/940 SRD MLO SWZU L150 WH	Temperature 650 °C, duration 30 s	SM340C
910925867896	SM340C 50S/940 SRD MLO SWZU L150 WH	Temperature 650 °C, duration 30 s	SM340C
910925867899	SM340C 35S/940 PSD-T MLO ACL L150 WH	Temperature 650 °C, duration 30 s	SM340C
910925867901	SM340C 45S/940 PSD-T MLO ACL L150 WH	Temperature 650 °C, duration 30 s	SM340C
910925867904	SM341C 26S/940 PSD MLO L150 WH	Temperature 650 °C, duration 30 s	SM341C
910925867912	SM341C 26S/940 SRD MLO SWZU L150 WH	Temperature 650 °C, duration 30 s	SM341C
910925867913	SM341C 35S/940 SRD MLO SWZU L150 WH	Temperature 650 °C, duration 30 s	SM341C

Order Code	Full Product Name	Glow-wire test	Product Family Code
910925867916	SM341C 26S/940 PSD-T MLO ACL L150 WH	Temperature 650 °C, duration 30 s	SM341C
910925867917	SM341C 35S/940 PSD-T MLO ACL L150 WH	Temperature 650 °C, duration 30 s	SM341C
910925867109	SM340C 35S/940 PSD MLO L150 SI	Temperature 650 °C, duration 30 s	SM340C
910925867875	SM340C 28S/940 PSD MLO L120 SI	Temperature 650 °C, duration 30 s	SM340C
910925867876	SM340C 36S/940 PSD MLO L120 SI	Temperature 650 °C, duration 30 s	SM340C
910925867889	SM340C 45S/940 PSD MLO L150 SI	Temperature 650 °C, duration 30 s	SM340C
910925867890	SM340C 50S/940 PSD MLO L150 SI	Temperature 650 °C, duration 30 s	SM340C
910925867908	SM341C 26S/940 PSD MLO L150 SI	Temperature 650 °C, duration 30 s	SM341C
910925867909	SM341C 35S/940 PSD MLO L150 SI	Temperature 650 °C, duration 30 s	SM341C
910925867110	SM340C 35S/940 PSD MLO L150 BK	Temperature 650 °C, duration 30 s	SM340C
910925867116	SM340C 35S/940 PSD O L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867867	SM340C 36S/940 PSD O L120 WH	Temperature 850 °C, duration 30 s	SM340C
910925867872	SM340C 36S/930 PSD O L120 WH	Temperature 850 °C, duration 30 s	SM340C
910925867886	SM340C 35S/930 PSD O L150 WH	Temperature 850 °C, duration 30 s	SM340C
910925867905	SM341C 26S/940 PSD O L150 WH	Temperature 850 °C, duration 30 s	SM341C
910925867877	SM340C 36S/940 PSD O L120 SI	Temperature 850 °C, duration 30 s	SM340C
910925867891	SM340C 35S/940 PSD O L150 SI	Temperature 850 °C, duration 30 s	SM340C
910925867892	SM340C 35S/940 PSD O L150 BK	Temperature 850 °C, duration 30 s	SM340C

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910925867099	SM340C 35S/940 PSD PCS L150 WH	4000 K	140 lm/W	3500 lm	25 W
910925867103	SM340C 35S/940 SRD	4000 K	143 lm/W	3500 lm	24.5 W

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910925867125	SM340C 35S/930 SRD PCS SWZU L150 WH	3000 K	135 lm/W	3500 lm	26 W

FlexBlend, Surface Mounted

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910925867134	SM340C 36S/940 PSD PCS L120 WH	4000 K	136 lm/W	3600 lm	26.5 W
910925867135	SM340C 42S/940 PSD PCS L120 WH	4000 K	131 lm/W	4200 lm	32 W
910925867865	SM340C 28S/940 PSD PCS L120 WH	4000 K	137 lm/W	2800 lm	20.5 W
910925867868	SM340C 28S/930 PSD PCS L120 WH	3000 K	127 lm/W	2800 lm	22 W
910925867869	SM340C 36S/930 PSD PCS L120 WH	3000 K	131 lm/W	3600 lm	27.5 W
910925867878	SM340C 45S/940 PSD PCS L150 WH	4000 K	138 lm/W	4500 lm	32.5 W
910925867879	SM340C 52S/940 PSD PCS L150 WH	4000 K	133 lm/W	5200 lm	39 W
910925867882	SM340C 35S/930 PSD PCS L150 WH	3000 K	130 lm/W	3500 lm	27 W
910925867883	SM340C 45S/930 PSD PCS L150 WH	3000 K	132 lm/W	4500 lm	34 W
910925867893	SM340C 45S/940 SRD PCS SWZU L150 WH	4000 K	141 lm/W	4500 lm	32 W
910925867894	SM340C 52S/940 SRD PCS SWZU L150 WH	4000 K	133 lm/W	5200 lm	39 W
910925867897	SM340C 35S/940 PSD-T PCS ACL L150 WH	4000 K	137 lm/W	3500 lm	25.5 W
910925867898	SM340C 45S/940 PSD-T PCS ACL L150 WH	4000 K	136 lm/W	4500 lm	33 W
910925867902	SM341C 26S/940 PSD PCS L150 WH	4000 K	133 lm/W	2600 lm	19.5 W
910925867903	SM341C 35S/940 PSD PCS L150 WH	4000 K	140 lm/W	3500 lm	25 W

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910925867910	SM341C 26S/940 SRD PCS SWZU L150 WH	4000 K	137 lm/W	2600 lm	19 W
910925867911	SM341C 35S/940 SRD PCS SWZU L150 WH	4000 K	143 lm/W	3500 lm	24.5 W
910925867914	SM341C 26S/940 PSD-T PCS ACL L150 WH	4000 K	130 lm/W	2600 lm	20 W
910925867915	SM341C 35S/940 PSD-T PCS ACL L150 WH	4000 K	137 lm/W	3500 lm	25.5 W
910925867101	SM340C 35S/940 PSD PCS L150 SI	4000 K	140 lm/W	3500 lm	25 W
910925867873	SM340C 28S/940 PSD PCS L120 SI	4000 K	137 lm/W	2800 lm	20.5 W
910925867874	SM340C 36S/940 PSD PCS L120 SI	4000 K	136 lm/W	3600 lm	26.5 W
910925867887	SM340C 45S/940 PSD PCS L150 SI	4000 K	138 lm/W	4500 lm	32.5 W
910925867888	SM340C 52S/940 PSD PCS L150 SI	4000 K	133 lm/W	5200 lm	39 W
910925867906	SM341C 26S/940 PSD PCS L150 SI	4000 K	133 lm/W	2600 lm	19.5 W
910925867907	SM341C 35S/940 PSD PCS L150 SI	4000 K	140 lm/W	3500 lm	25 W
910925867102	SM340C 35S/940 PSD PCS L150 BK	4000 K	140 lm/W	3500 lm	25 W
910925867108	SM340C 35S/940 PSD MLO L150 WH	4000 K	108 lm/W	3500 lm	32.5 W
910925867111	SM340C 35S/940 SRD MLO SWZU L150 WH	4000 K	109 lm/W	3500 lm	32 W
910925867136	SM340C 36S/940 PSD MLO L120 WH	4000 K	103 lm/W	3600 lm	35 W

FlexBlend, Surface Mounted

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910925867137	SM340C 40S/940 PSD MLO L120 WH	4000 K	103 lm/W	4000 lm	39 W
910925867262	SM341C 35S/940 PSD MLO L150 WH	4000 K	108 lm/W	3500 lm	32.5 W
910925867866	SM340C 28S/940 PSD MLO L120 WH	4000 K	106 lm/W	2800 lm	26.5 W
910925867870	SM340C 28S/930 PSD MLO L120 WH	3000 K	102 lm/W	2800 lm	27.5 W
910925867871	SM340C 36S/930 PSD MLO L120 WH	3000 K	98.5 lm/W	3600 lm	36.5 W
910925867880	SM340C 45S/940 PSD MLO L150 WH	4000 K	105 lm/W	4500 lm	43 W
910925867881	SM340C 50S/940 PSD MLO L150 WH	4000 K	104 lm/W	5000 lm	48 W
910925867884	SM340C 35S/930 PSD MLO L150 WH	3000 K	103 lm/W	3500 lm	34 W
910925867885	SM340C 45S/930 PSD MLO L150 WH	3000 K	100 lm/W	4500 lm	45 W
910925867895	SM340C 45S/940 SRD MLO SWZU L150 WH	4000 K	106 lm/W	4500 lm	42.5 W
910925867896	SM340C 50S/940 SRD MLO SWZU L150 WH	4000 K	104 lm/W	5000 lm	48 W
910925867899	SM340C 35S/940 PSD-T MLO ACL L150 WH	4000 K	106 lm/W	3500 lm	33 W
910925867901	SM340C 45S/940 PSD-T MLO ACL L150 WH	4000 K	103 lm/W	4500 lm	43.5 W
910925867904	SM341C 26S/940 PSD MLO L150 WH	4000 K	107 lm/W	2600 lm	24 W
910925867912	SM341C 26S/940 SRD MLO SWZU L150 WH	4000 K	111 lm/W	2600 lm	23.5 W

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910925867913	SM341C 35S/940 SRD MLO SWZU L150 WH	4000 K	109 lm/W	3500 lm	32 W
910925867916	SM341C 26S/940 PSD-T MLO ACL L150 WH	4000 K	106 lm/W	2600 lm	24.5 W
910925867917	SM341C 35S/940 PSD-T MLO ACL L150 WH	4000 K	106 lm/W	3500 lm	33 W
910925867109	SM340C 35S/940 PSD MLO L150 SI	4000 K	108 lm/W	3500 lm	32.5 W
910925867875	SM340C 28S/940 PSD MLO L120 SI	4000 K	106 lm/W	2800 lm	26.5 W
910925867876	SM340C 36S/940 PSD MLO L120 SI	4000 K	103 lm/W	3600 lm	35 W
910925867889	SM340C 45S/940 PSD MLO L150 SI	4000 K	105 lm/W	4500 lm	43 W
910925867890	SM340C 50S/940 PSD MLO L150 SI	4000 K	104 lm/W	5000 lm	48 W
910925867908	SM341C 26S/940 PSD MLO L150 SI	4000 K	107 lm/W	2600 lm	24 W
910925867909	SM341C 35S/940 PSD MLO L150 SI	4000 K	108 lm/W	3500 lm	32.5 W
910925867110	SM340C 35S/940 PSD MLO L150 BK	4000 K	108 lm/W	3500 lm	32.5 W
910925867116	SM340C 35S/940 PSD O L150 WH	4000 K	125 lm/W	3500 lm	28 W
910925867867	SM340C 36S/940 PSD O L120 WH	4000 K	126 lm/W	3600 lm	28.5 W
910925867872	SM340C 36S/930 PSD O L120 WH	3000 K	116 lm/W	3600 lm	31 W
910925867886	SM340C 35S/930 PSD O L150 WH	3000 K	123 lm/W	3500 lm	28.5 W

FlexBlend, Surface Mounted

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910925867905	SM341C 26S/940 PSD O L150 WH	4000 K	121 lm/W	2600 lm	21.5 W
910925867877	SM340C 36S/940 PSD O L120 SI	4000 K	126 lm/W	3600 lm	28.5 W

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910925867891	SM340C 35S/940 PSD O L150 SI	4000 K	125 lm/W	3500 lm	28 W
910925867892	SM340C 35S/940 PSD O L150 BK	4000 K	125 lm/W	3500 lm	28 W

Mechanical and Housing

Order Code	Full Product Name	Color
910925867099	SM340C 35S/940 PSD PCS L150 WH	White RAL 9003
910925867103	SM340C 35S/940 SRD PCS SWZU L150 WH	White RAL 9003
910925867125	SM340C 35S/930 SRD PCS SWZU L150 WH	White RAL 9003
910925867134	SM340C 36S/940 PSD PCS L120 WH	White RAL 9003
910925867135	SM340C 42S/940 PSD PCS L120 WH	White RAL 9003
910925867865	SM340C 28S/940 PSD PCS L120 WH	White RAL 9003
910925867868	SM340C 28S/930 PSD PCS L120 WH	White RAL 9003
910925867869	SM340C 36S/930 PSD PCS L120 WH	White RAL 9003
910925867878	SM340C 45S/940 PSD PCS L150 WH	White RAL 9003
910925867879	SM340C 52S/940 PSD PCS L150 WH	White RAL 9003
910925867882	SM340C 35S/930 PSD PCS L150 WH	White RAL 9003
910925867883	SM340C 45S/930 PSD PCS L150 WH	White RAL 9003
910925867893	SM340C 45S/940 SRD PCS SWZU L150 WH	White RAL 9003
910925867894	SM340C 52S/940 SRD PCS SWZU L150 WH	White RAL 9003
910925867897	SM340C 35S/940 PSD-T PCS ACL L150 WH	White RAL 9003
910925867898	SM340C 45S/940 PSD-T PCS ACL L150 WH	White RAL 9003
910925867902	SM341C 26S/940 PSD PCS L150 WH	White RAL 9003
910925867903	SM341C 35S/940 PSD PCS L150 WH	White RAL 9003
910925867910	SM341C 26S/940 SRD PCS SWZU L150 WH	White RAL 9003
910925867911	SM341C 35S/940 SRD PCS SWZU L150 WH	White RAL 9003
910925867914	SM341C 26S/940 PSD-T PCS ACL L150 WH	White RAL 9003
910925867915	SM341C 35S/940 PSD-T PCS ACL L150 WH	White RAL 9003
910925867101	SM340C 35S/940 PSD PCS L150 SI	Silver RAL 9006
910925867873	SM340C 28S/940 PSD PCS L120 SI	Silver RAL 9006
910925867874	SM340C 36S/940 PSD PCS L120 SI	Silver RAL 9006
910925867887	SM340C 45S/940 PSD PCS L150 SI	Silver RAL 9006
910925867888	SM340C 52S/940 PSD PCS L150 SI	Silver RAL 9006
910925867906	SM341C 26S/940 PSD PCS L150 SI	Silver RAL 9006
910925867907	SM341C 35S/940 PSD PCS L150 SI	Silver RAL 9006
910925867102	SM340C 35S/940 PSD PCS L150 BK	Black RAL 9004
910925867108	SM340C 35S/940 PSD MLO L150 WH	White RAL 9003
910925867111	SM340C 35S/940 SRD MLO SWZU L150 WH	White RAL 9003
910925867136	SM340C 36S/940 PSD MLO L120 WH	White RAL 9003
910925867137	SM340C 40S/940 PSD MLO L120 WH	White RAL 9003

Order Code	Full Product Name	Color
910925867262	SM341C 35S/940 PSD MLO L150 WH	White RAL 9003
910925867866	SM340C 28S/940 PSD MLO L120 WH	White RAL 9003
910925867870	SM340C 28S/930 PSD MLO L120 WH	White RAL 9003
910925867871	SM340C 36S/930 PSD MLO L120 WH	White RAL 9003
910925867880	SM340C 45S/940 PSD MLO L150 WH	White RAL 9003
910925867881	SM340C 50S/940 PSD MLO L150 WH	White RAL 9003
910925867884	SM340C 35S/930 PSD MLO L150 WH	White RAL 9003
910925867885	SM340C 45S/930 PSD MLO L150 WH	White RAL 9003
910925867895	SM340C 45S/940 SRD MLO SWZU L150 WH	White RAL 9003
910925867896	SM340C 50S/940 SRD MLO SWZU L150 WH	White RAL 9003
910925867899	SM340C 35S/940 PSD-T MLO ACL L150 WH	White RAL 9003
910925867901	SM340C 45S/940 PSD-T MLO ACL L150 WH	White RAL 9003
910925867904	SM341C 26S/940 PSD MLO L150 WH	White RAL 9003
910925867912	SM341C 26S/940 SRD MLO SWZU L150 WH	White RAL 9003
910925867913	SM341C 35S/940 SRD MLO SWZU L150 WH	White RAL 9003
910925867916	SM341C 26S/940 PSD-T MLO ACL L150 WH	White RAL 9003
910925867917	SM341C 35S/940 PSD-T MLO ACL L150 WH	White RAL 9003
910925867109	SM340C 35S/940 PSD MLO L150 SI	Silver RAL 9006
910925867875	SM340C 28S/940 PSD MLO L120 SI	Silver RAL 9006
910925867876	SM340C 36S/940 PSD MLO L120 SI	Silver RAL 9006
910925867889	SM340C 45S/940 PSD MLO L150 SI	Silver RAL 9006
910925867890	SM340C 50S/940 PSD MLO L150 SI	Silver RAL 9006
910925867908	SM341C 26S/940 PSD MLO L150 SI	Silver RAL 9006
910925867909	SM341C 35S/940 PSD MLO L150 SI	Silver RAL 9006
910925867110	SM340C 35S/940 PSD MLO L150 BK	Black RAL 9004
910925867116	SM340C 35S/940 PSD O L150 WH	White RAL 9003
910925867867	SM340C 36S/940 PSD O L120 WH	White RAL 9003
910925867872	SM340C 36S/930 PSD O L120 WH	White RAL 9003
910925867886	SM340C 35S/930 PSD O L150 WH	White RAL 9003
910925867905	SM341C 26S/940 PSD O L150 WH	White RAL 9003
910925867877	SM340C 36S/940 PSD O L120 SI	Silver RAL 9006
910925867891	SM340C 35S/940 PSD O L150 SI	Silver RAL 9006
910925867892	SM340C 35S/940 PSD O L150 BK	Black RAL 9004

FlexBlend, Surface Mounted

