



TOUCH PEN,
THIN FOR RESISTIVE TOUCHSCREEN HOLDING CORD
FOR MOBILE PANEL 277 10" AND OTHER TOUCH
DISPLAYS AMOUNT AND CONTENT: SEE TECHNICAL
DATA

Installation type/mounting	
Wall mounting/direct mounting possible	Yes ; using 40 cm retaining cord
Standards, approvals, certificates	
CE	Yes
Ambient conditions	
Operating temperature	
Operating temperature range, min.	0 °C
Operating temperature range, max.	55 °C
Storage/transport temperature	
Min.	-20 °C
max.	70 °C
Relative humidity	
max. relative humidity	90 %
Mechanics/material	
Plastic	Yes
Dimensions	
Height	125 mm ; Length
Thickness	8 mm ; Diameter

Scope of supply	
Delivery unit in items	5 ; Incl. retaining cord for Mobile Panel 277 10"
other	
Note:	for resistive touch screens
Usable in the following products	
Product 1	6AV6642-0AA11-0AX0
Product 2	6AV6642-0AA11-0AX1
Product 3	6AV6642-0BD01-3AX0
Product 4	6AV6642-0BA01-1AX1
Product 5	6AV6642-0BC01-1AX1
Product 6	6AV6642-0DC01-1AX0
Product 7	6AV6642-0DA01-1AX0
Product 8	6AV6545-0DA10-0AX0
Product 9	6AV6545-0DB10-0AX0
Product 10	6AV6545-0AA15-2AX0
Product 12	6AV6642-0EA01-3AX0
Product 13	6AV6644-0CB01-2AX0
Product 15	6AV6640-0CA01-0AX0
Product 16	6AV6545-0AH10-0AX0
	6AV6545-0AH10-0AX1
Product 18	6AV6640-0CA01-0AX0
Product 19	6AV6545-0CC10-0AX0
Status	Oct 28, 2013