

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

blackbolt@Kontaktrens m/smøring spray

Product no.

-

REACH registration number

Not applicable

Other means of identification

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

NA

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Pureno A/S
Rønnevangs Alle 8
3400 Hillerød
Denmark
Tlf.: +45 70 260 267:

Contact person

Kenneth Christensen

E-mail

mail@pureno.dk

SDS date

19-06-2015

SDS Version

2.0

1.4. Emergency telephone number

Use your national or local emergency number
See section 4 "First aid measures"

SECTION 2: Hazards identification

▼ 2.1. Classification of the substance or mixture

Aerosol 1; H229
Aerosol 1; H222
Eye Irrit. 2; H319
STOT SE 3; H336
EUH066

See full text of H-phrases in section 2.2.

2.2. Label elements

▼ Hazard pictogram(s)



▼ **Signal word**

Danger

▼ **Hazard statement(s)**

Pressurised container: May burst if heated. (H229)

Extremely flammable aerosol. (H222)

Causes serious eye irritation. (H319)

May cause drowsiness or dizziness. (H336)

▼ Safety statement(s)	General	If medical advice is needed, have product container or label at hand. (P101). Keep out of reach of children. (P102).
	Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210).
	Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338).
	Storage	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. (P410+P412).
	Disposal	Dispose of contents/container to an approved waste disposal plant. (P501).

▼ **Identity of the substances primarily responsible for the major health hazards**

Naphtha (petroleum), hydrotreated heavy (0,1<benzen)

2.3. Other hazards

This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys.

▼ **Additional labelling**

Repeated exposure may cause skin dryness or cracking. (EUH066)

Additional warnings

VOC

-

SECTION 3: Composition/information on ingredients

▼ **3.1/3.2. Substances/Mixtures**

NAME:	ethanol
IDENTIFICATION NOS.:	CAS-no: 64-17-5 EC-no: 200-578-6 Index-no: 603-002-00-5
CONTENT:	40-60%
CLP CLASSIFICATION:	Flam. Liq. 2, Eye Irrit. 2 H225, H319
NOTE:	S
NAME:	Naphtha (petroleum), hydrotreated heavy (0,1<benzen)
IDENTIFICATION NOS.:	CAS-no: 64742-48-9 EC-no: 265-150-3 Index-no: 649-327-00-6
CONTENT:	25-40%
CLP CLASSIFICATION:	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1 H226, H304, H336, EUH066
NAME:	propan-2-ol
IDENTIFICATION NOS.:	CAS-no: 67-63-0 EC-no: 200-661-7 Index-no: 603-117-00-0
CONTENT:	15-25%
CLP CLASSIFICATION:	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 H225, H319, H336
NOTE:	S
NAME:	paraffinolie (råolie)
IDENTIFICATION NOS.:	CAS-no: 8042-47-5 EC-no: 232-455-8
CONTENT:	10-15%

According to EC-Regulation 1907/2006 (REACH)

CLP CLASSIFICATION:	NA
NAME:	carbon dioxide
IDENTIFICATION NOS.:	CAS-no: 124-38-9 EC-no: 204-696-9
CONTENT:	5-10%
CLP CLASSIFICATION:	Comp. Gas H280

(*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.
S = Organic solvent

Other informations

SECTION 4: First aid measures

4.1. Description of first aid measures

▼ General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the person into fresh air and stay with them.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

▼ Eye contact

Remove contact lenses. Flush eyes with water (20-30°C) for at least 15 minutes. Call a doctor.

Burns

Rinse with water until the pain stops and continue for 30 minutes.

▼ 4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens. Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

▼ 6.1. Personal precautions, protective equipment and emergency procedures

According to EC-Regulation 1907/2006 (REACH)

Avoid inhalation of vapours from waste material. Stores that have not ignited must be cooled by water mist. Where possible, remove flammable materials. Make sure there is sufficient ventilation.

▼ 6.2. Environmental precautions

No specific requirements.

▼ 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

▼ 6.4. Reference to other sections

See section on "Disposal" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

▼ 7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection.

▼ 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Must be stored in a cool and ventilated area, away from possible sources of combustion.

▼ Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

carbon dioxide (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 5000 ppm | 9150 mg/m³

Short-term exposure limit (15-minute reference period): 15000 ppm | 27400 mg/m³

ethanol (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 1000 ppm | 1920 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

DNEL / PNEC

No data available.

8.2. Exposure controls

▼ Compliance with the stated exposure limits values should be checked on a regular basis.

General recommendations

▼ Observe general occupational hygiene.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

According to EC-Regulation 1907/2006 (REACH)



▼ Generally

Use only CE marked protective equipment.

Respiratory Equipment

If the ventilation at the work place is not sufficient, use a half or whole mask with an appropriate filter or an air-supplied respiratory protector. The choice depends on the concrete work situation and how long you will be using the product.

▼ Skin protection

Special work clothing should be used.

Hand protection

Recommended: Nitrile rubber. : NA

Eye protection

Use face shield. Use safety glasses with a side shield as an alternative.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm ³)
Aerosol	Clear	Alcohol odor	-	-	-

Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	-	-

Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
16	-	-
Explosion limits (Vol %)	Oxidizing properties	
-	-	

Solubility

Solubility in water	n-octanol/water coefficient
Insoluble	-

9.2. Other information

Solubility in fat	Additional information
-	N/A

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

▼ 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

▼ Acute toxicity

Substance	Species	Test	Route of exposure	Result
-----------	---------	------	-------------------	--------

According to EC-Regulation 1907/2006 (REACH)

paraffinolie (råolie)	Rat	LD50	Oral	>5000 mg/kg
propan-2-ol	Rabbit	LD50	Dermal	12800 mg/kg bdw
propan-2-ol	Rat	LD50	Oral	5045 mg/kg bdw
propan-2-ol	Rat	LC50	Inhalation	16000 ppm/8H
Naphtha (petroleum), hydrotrea...	Rat	LD50	Oral	>5000mg/kg
Naphtha (petroleum), hydrotrea...	Rat	LC50	Inhalation	>5mg/L
Naphtha (petroleum), hydrotrea...	Rat	LD50	Dermal	>5000mg/kg
ethanol	Rat	LD50	Oral	7060mg/kg bdw
ethanol	Rabbit	LD lo	Dermal	20mg/kg bdw
ethanol	Rat	LC50	Inhalation	20000 ppm/10 H

▼ Skin corrosion/irritation

No data available.

▼ Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

▼ STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

▼ Long term effects

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

SECTION 12: Ecological information

▼ 12.1. Toxicity

Substance	Species	Test	Test duration	Result
propan-2-ol	Fish	LC50	48h	1400000 ug/L
propan-2-ol	Algae	EC50	24h	1000000 ug/L
Naphtha (petroleum), hydrotrea...	Daphnia	EC0	48H	1000mg/L

▼ 12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
propan-2-ol	Yes	No data available	No data available
ethanol	Yes	No data available	No data available

▼ 12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BFC
propan-2-ol	No	No data available	No data available
Naphtha (petroleum), hydrotrea...	No	No data available	No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

Waste

EWC code

16.05.04

Specific labelling

-

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

SECTION 14: Transport information

This product is covered by the conventions on dangerous goods.

14.1 – 14.4

▼ ADR/RID

14.1. UN number 1950

14.2. UN proper shipping name

14.3. Transport hazard class(es) 2.1

14.4. Packing group

Notes

Tunnel restriction code -

IMDG

UN-no. 1950

Proper Shipping Name Aerosoler

Class 2.1

PG*

EmS F-D, S-U

MP** -

Hazardous constituent -

▼ IATA/ICAO

UN-no.

Proper Shipping Name

Class

PG*

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

▼ Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC.

Demands for specific education

-

Additional information

-

Sources

According to EC-Regulation 1907/2006 (REACH)

EC regulation 1907/2006 (REACH)

Directive 2000/532/EC

EC Regulation 1272/2008 (CLP)

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H225 - Highly flammable liquid and vapour.

H226 - Flammable liquid and vapour.

H280 - Contains gas under pressure; may explode if heated.

H304 - May be fatal if swallowed and enters airways.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

EUH066 - Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

-

Other symbols mentioned in section 2



Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by

JS

Date of last essential change (First cipher in SDS version)

03-09-2014

Date of last minor change (Last cipher in SDS version)

19-06-2015