

SIMATIC S7-1500F, CPU 1518F-4 PN/DP, CENTRAL PROCESSING UNIT WITH WORKING MEMORY 4,5 MB FOR PROGRAM AND 10 MB FOR DATA, 1. INTERFACE, PROFINET IRT WITH 2 PORT SWITCH, 2. INTERFACE, ETHERNET, 3. INTERFACE, ETHERNET, 4. INTERFACE, PROFIBUS, 1 NS BIT-PERFORMANCE, SIMATIC MEMORY CARD NECESSARY



Product type designation	
General information	
Hardware product version	FS01
Firmware version	V1.6
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal can be configured/integrated as of version 	V13 Update 3
Display	
Screen diagonal (cm)	6.1 cm
Control elements	
Number of keys	6
Mode selector switch	1
Supply voltage	
Type of supply voltage	24 V DC
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	

Inrush current, max.	2.4 A; Rated value
Power	
Power consumption from the backplane bus (balanced)	30 W
Infeed power to the backplane bus	12 W
Power losses	
Power loss, typ.	24 W
Memory	
SIMATIC Memory Card required	Yes
Work memory	
• integrated (for program)	4.5 Mbyte
• integrated (for data)	10 Mbyte
Load memory	
• Plug-in (SIMATIC Memory Card), max.	32 Gbyte
Backup	
• maintenance-free	Yes
CPU processing times	
for bit operations, typ.	1 ns
for word operations, typ.	2 ns
for fixed point arithmetic, typ.	2 ns
for floating point arithmetic, typ.	6 ns
CPU-blocks	
Number of blocks (total)	10 000
DB	
• Number, max.	10 000; Number range: 1 to 65535
• Size, max.	10 Mbyte
FB	
• Number, max.	9 998; Number range: 1 to 65535
• Size, max.	512 kbyte
FC	
• Number, max.	9 999; Number range: 1 to 65535
• Size, max.	512 kbyte
OB	
• Size, max.	512 kbyte
• Number of free cycle OBs	100
• Number of time alarm OBs	20
• Number of delay alarm OBs	20
• Number of time interrupt OBs	20
• Number of process alarm OBs	50
• Number of DPV1 alarm OBs	3
• Number isochronous mode OBs	2
• Number of technology synchronous alarm OBs	2

• Number of startup OBs	100
• Number of asynchronous error OBs	4
• Number of synchronous error OBs	2
• Number of diagnostic alarm OBs	1
Nesting depth	
• per priority class	24; only 8 for F-blocks

Counters, timers and their retentivity

S7 counter	
• Number	2 048
Retentivity	
— can be set	Yes
IEC counter	
• Number	Any (only limited by the main memory)
Retentivity	
— can be set	Yes
S7 times	
• Number	2 048
Retentivity	
— can be set	Yes
IEC timer	
• Number	Any (only limited by the main memory)
Retentivity	
— can be set	Yes

Data areas and their retentivity

retentive data area in total (incl. times, counters, flags), max.	768 kbyte; Available retentive memory for bit memories, timers, counters, DBs, and technology data (axes): 700 KB
Flag	
• Number, max.	16 kbyte
• Number of clock memories	8
Data blocks	
• Retentivity adjustable	Yes
• Retentivity preset	No
Local data	
• per priority class, max.	64 kbyte; max. 16 KB per block

Address area

Number of IO modules	8 192
I/O address area	
• Inputs	32 kbyte; All inputs are in the process image
• Outputs	32 kbyte; All outputs are in the process image
per integrated IO subsystem	
— Inputs (volume)	16 kbyte; 16 KB via the integrated PROFINET IO interface, 8 KB via the integrated DP interface

— Outputs (volume)	16 kbyte; 16 KB via the integrated PROFINET IO interface, 8 KB via the integrated DP interface
per CM/CP	
— Inputs (volume)	8 kbyte
— Outputs (volume)	8 kbyte
Subprocess images	
• Number of subprocess images, max.	32
Address space per module	
• Number of IO subsystems	10
Hardware configuration	
Number of DP masters	
• Integrated	1
• via CM	8; A maximum of 8 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total
Number of IO Controllers	
• Integrated	1
• via CM	8; A maximum of 8 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total
Rack	
• Modules per rack, max.	32; CPU + 31 modules
• Rack, number of rows, max.	1
PtP CM	
• Number of PtP CMs	the number of connectable PtP CMs is only limited by the number of available slots
Time of day	
Clock	
• Type	Hardware clock
• Deviation per day, max.	10 s; Typ.: 2 s
• Backup time	6 wk; At 40 °C ambient temperature, typically
Operating hours counter	
• Number	16
Clock synchronization	
• supported	Yes
• to DP, master	Yes
• in AS, master	Yes
• in AS, slave	Yes
• on Ethernet via NTP	Yes
Interfaces	
Number of PROFINET interfaces	3
Number of PROFIBUS interfaces	1
1st interface	
Interface types	
— Number of ports	2

— Integrated switch	Yes
— RJ 45 (Ethernet)	Yes
Protocols	
— PROFINET IO Controller	Yes
— PROFINET IO Device	Yes
— SIMATIC communication	Yes
— Open IE communication	Yes
— Web server	Yes
— Media redundancy	Yes
2nd interface	
Interface types	
— Number of ports	1
— Integrated switch	No
— RJ 45 (Ethernet)	Yes
Protocols	
— PROFINET IO Controller	No
— PROFINET IO Device	No
— SIMATIC communication	Yes
— Open IE communication	Yes
— Web server	Yes
3rd interface	
Interface types	
— Number of ports	1
— Integrated switch	No
— RJ 45 (Ethernet)	Yes
Protocols	
— PROFINET IO Controller	No
— PROFINET IO Device	No
— SIMATIC communication	Yes
— Open IE communication	Yes
— Web server	Yes
4th interface	
Interface types	
— Number of ports	1
— RS 485	Yes
Protocols	
— SIMATIC communication	Yes
— PROFIBUS DP master	Yes
— PROFIBUS DP slave	No
Interface types	
RJ 45 (Ethernet)	
• 100 Mbps	Yes
• Autonegotiation	Yes

• Autocrossing	Yes
• Industrial Ethernet status LED	Yes
RS 485	
• Transmission rate, max.	12 Mbit/s
Protocols	
Number of connections	
• Number of connections, max.	384; via integrated interfaces of the CPU and connected CPs / CMs
• Number of connections reserved for ES/HMI/web	10
• Number of connections via integrated interfaces	192
• Number of S7 routing paths	64
PROFINET IO Controller	
Services	
— PG/OP communication	Yes
— S7 routing	Yes
— Isochronous mode	Yes
— Open IE communication	Yes
— IRT	Yes
— MRP	Yes; As MRP redundancy manager and/or MRP client; max. number of devices in the ring: 50
— PROFINergy	Yes
— Prioritized startup	Yes; Max. 32 PROFINET devices
— Number of connectable IO devices, max.	512; In total, up to 1000 distributed I/O devices can be connected via PROFIBUS or PROFINET
— Max. number of connectable IO devices for RT	512
— of which in line, max.	512
— Number of IO Devices with IRT and the option "high performance", max.	64
— Maximum number of IO devices that can be activated/deactivated at the same time.	8
— Max. number of IO devices per tool	8
— Updating times	The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data
with RT	
— for send cycle of 250 µs	250 µs to 128 ms
— for send cycle of 500 µs	500 µs to 256 ms
— for send cycle of 1 ms	1 ms to 512 ms
— for send cycle of 2 ms	2 ms to 512 ms
— for send cycle of 4 ms	4 ms to 512 ms
for IRT with the "high performance" option	

— for send cycle of 250 µs	250 µs to 4 ms
— for send cycle of 500 µs	500 µs to 8 ms
— for send cycle of 1 ms	1 ms to 16 ms
— for send cycle of 2 ms	2 ms to 32 ms
— for send cycle of 4 ms	4 ms to 64 ms
— For IRT with the "high performance" option and parameter assignment for so-called "odd-numbered" send cycles	Update time = set "odd" send clock (any multiple of 125 µs: 375 µs, 625 µs ... 3.875 µs)

PROFINET IO Device

Services

— PG/OP communication	Yes
— S7 routing	Yes
— Isochronous mode	No
— Open IE communication	Yes
— IRT, supported	Yes
— MRP, supported	Yes
— PROFinergy	Yes
— Shared device	Yes
— Number of IO controllers with shared device, max.	4

SIMATIC communication

• S7 communication, as server	Yes
• S7 communication, as client	Yes
• User data per job, max.	See online help (S7 communication, user data size)

Open IE communication

• TCP/IP	Yes
— Data length, max.	64 kbyte
— several passive connections per port, supported	Yes
• ISO-on-TCP (RFC1006)	Yes
— Data length, max.	64 kbyte
• UDP	Yes
— Data length, max.	1 472 byte
• DHCP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes

Web server

• HTTP	Yes; Standard and user-defined pages
• HTTPS	Yes; Standard and user-defined pages

PROFIBUS

Services

— PG/OP communication	Yes
— S7 routing	Yes

— Data record routing	Yes
— Isochronous mode	Yes
— equidistance	Yes
— Number of DP slaves	125; In total, up to 1000 distributed I/O devices can be connected via PROFIBUS or PROFINET
— Activation/deactivation of DP slaves	Yes
PROFIBUS DP master	
• Number of connections, max.	48; for the integrated PROFIBUS DP interface
Further protocols	
• MODBUS	Yes; MODBUS TCP
Media redundancy	
• Switchover time on line break, typically	200 ms
• Number of stations in the ring, max.	50
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
equidistance	Yes
S7 message functions	
Number of login stations for message functions, max.	32
Block related messages	Yes
Number of configurable alarms, max.	10 000
Number of simultaneously active alarms in alarm pool	
• Number of reserved user alarms	1 000
• Number of reserved alarms for system diagnostics	200
• Number of reserved alarms for motion technology objects	160
Test commissioning functions	
Joint commission (Team Engineering)	
• Maximum number of parallel ES clients	5
Status block	Yes; Up to 8 simultaneously (in total across all ES clients)
Single step	No
Status/control	
• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• of which status variables, max.	200; per job
• of which control variables, max.	200; per job
Forcing	
• Force, variables	Inputs, outputs
• Number of variables, max.	200
Diagnostic buffer	
• present	Yes

programming	
Programming language	
— LAD	Yes; incl. failsafe
— FBD	Yes; incl. failsafe
— STL	Yes
— SCL	Yes
— GRAPH	Yes
Know-how protection	
• User program protection	Yes
• Copy protection	Yes
• Block protection	Yes
Access protection	
• Password for display	Yes
• Protection level: Write protection	Yes
• Protection level: Read/write protection	Yes
• Protection level: Complete protection	Yes
Cycle time monitoring	
• lower limit	adjustable minimum cycle time
• upper limit	adjustable maximum cycle time
Dimensions	
Width	175 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	830 g
last modified:	25.10.2014