

Indexing plungers, stainless steel, Form C

Item description/product images



Description

Material:

Indexing pin hardened:
Threaded sleeve 1.4305.
Indexing pin 1.4034.

Indexing pin not hardened:
Threaded sleeve 1.4305.
Indexing pin 1.4305.

Mushroom knob 1.4305, electropolished.

Version:

Bright.
Indexing pin ground.

Note:


Indexing plungers are used to prevent any change in locking position due to lateral forces. A new locking position can only be set after the pin has been manually disengaged. Form C or D is recommended for applications in which the pin is disengaged over extended periods and should be prevented from springing back.

On request:

Special versions.

Drawings

Form C
lockout type
without locknut



Overview of items

Order No.	Form	Main material	locating pin	D	D1	D2	L	L1	L2	L3	Travel S	SW1	Fx30°	Spring force initial pressure F1 approx. N	Spring force final pressure F2 approx. N
K0632.003903	C	stainless steel	hardened	3	M6x0,75	14	31,5	12	5	10	3,5	8	0,8	4,5	10

Indexing plungers, stainless steel, Form C

Overview of items

Order No.	Form	Main material	locating pin	D	D1	D2	L	L1	L2	L3	Travel S	SW1	Fx30°	Spring force initial pressure F1 approx. N	Spring force final pressure F2 approx. N
K0632.003004	C	stainless steel	hardened	4	M8x1	18	38,5	15	6	13	4	10	1	6	12
K0632.003105	C	stainless steel	hardened	5	M10x1	21	43,5	17	7	15	5	13	1,3	5	12
K0632.003206	C	stainless steel	hardened	6	M12x1,5	25	51,7	20	8	17	6	14	1,8	6	14
K0632.003308	C	stainless steel	hardened	8	M16x1,5	33	68	26	10	23	8	19	2,3	15	35
K0632.003410	C	stainless steel	hardened	10	M20x1,5	33	74	28	12	25	10	22	2,8	15	34
K0632.003412	C	stainless steel	hardened	12	M20x1,5	33	78	28	14	25	12	22	2,8	15	39
K0632.003516	C	stainless steel	hardened	16	M24x2	40	96	32	18	28	16	27	3,2	20	46
K0632.113903	C	stainless steel	not hardened	3	M6x0,75	14	31,5	12	5	10	3,5	8	0,8	4,5	10
K0632.113004	C	stainless steel	not hardened	4	M8x1	18	38,5	15	6	13	4	10	1	6	12
K0632.113105	C	stainless steel	not hardened	5	M10x1	21	43,5	17	7	15	5	13	1,3	5	12
K0632.113206	C	stainless steel	not hardened	6	M12x1,5	25	51,7	20	8	17	6	14	1,8	6	14
K0632.113308	C	stainless steel	not hardened	8	M16x1,5	33	68	26	10	23	8	19	2,3	15	35
K0632.113410	C	stainless steel	not hardened	10	M20x1,5	33	74	28	12	25	10	22	2,8	15	34
K0632.113412	C	stainless steel	not hardened	12	M20x1,5	33	78	28	14	25	12	22	2,8	15	39
K0632.113516	C	stainless steel	not hardened	16	M24x2	40	96	32	18	28	16	27	3,2	20	46