

Combination spanner

Item description/product images



Description

Material:

Tool steel.

Note:

The protective cap was specially developed for tightening and loosening screw connections with sensitive surfaces. With normal tools, the surface of polished screws are so damaged from the first tightening, that cavities are created making easy and effective cleaning no longer possible.

The protective caps ensure damage free tightening and loosening of fasteners with outer contours. The soft aluminium leaves no scratches or other damage on sensitive surfaces. By correct and professional use the protective caps have a service life of ca. 1000 operating cycles.


Additionally, with the protective caps the risk of contact corrosion is reliably prevented on stainless steel fasteners. The projecting contour largely prevents unintentional contact points between spanner and stainless steel screw. The protective caps are made of the aluminium alloy EN AW 6082 and so comply with EN 602 - aluminium in contact with food.

The protective cap is held securely in the spanner by a special moulding or spring clip element. The cap cannot fall out on its own. Worn-out protective caps are changed manually.

On request:

Other sizes.

Drawings



Overview of items

Order No.	Item	SW	A	B	L	D
K1362.10	Ring Spanner	10	5	8	154,5	5
K1362.11	Ring Spanner	11	5,5	8,4	168,5	5
K1362.13	Ring Spanner	13	6,3	10	193	6
K1362.16	Ring Spanner	16	7	11,4	230,5	6
K1362.19	Ring Spanner	19	8	13,5	268,5	7
K1362.21	Ring Spanner	21	8,5	13,7	292	7
K1362.27	Ring Spanner	27	10,5	16	380	9

