M12 CH-0 | M12 FUEL™ sub compact SDS-plus hammer

Article: 4933441947



- Industry's first brushless compact 12V rotary hammer with 1.1 Joules (EPTA), 0 - 6575 bpm & 0 - 900 rpm.
- Flexible battery system: works with all Milwaukee® M12™ batteries.
- Exceptionally low vibration value 4.4 m/s² can be used for 8 hours in a day.
- Will drill over 60 50 mm x 6 mm holes per battery charge.
- Superior power to weight ratio in its class with Milwaukee® designed and built brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more run time.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.

| | M12 CH-0 |
|---|------------|
| Sound pressure level (dB(A)) | 84.5 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Sound power level (dB(A)) | 95.5 |
| Sound power level uncertainty (dB(A)) | 3 |
| Vibration drilling into concrete uncertainty [m s²] | 1.5 |
| No load speed (rpm) | 0 - 900 |
| Voltage (V) | 12 |
| Battery pack capacity (Ah) | _ |
| Battery type | Li-ion |
| Optimised drilling capacity in concrete (mm) | ø 5.5 - 12 |
| Supplied in | - |
| Charger supplied | _ |
| No. of batteries supplied | 0 |
| Vibration drilling (m/s²) | 4.4 |
| Article Number | 4933441947 |
| Weight with battery pack (kg) | _ |
| Max. drilling steel (mm) | 10 |
| Max. drilling wood (mm) | 13 |
| Max. drilling concrete (mm) | 13 |
| Full load hammer action (bpm) | 0 - 6575 |
| Blow energy (EPTA)(J) | 1.1 |
| | |

