

# SIEMENS

## Product data sheet

**6ES7134-6JD00-0CA1**


SIMATIC ET 200SP, ANALOG INPUT MODULE,  
AI 4XRTD/TC HIGH FEATURE,  
FITS TO BU-TYPE A0, A1,  
COLOR CODE CC00, CHANNEL DIAGNOSIS,  
16BIT, +/-0,1%, 2-/3-/4-WIRE

### CiR - Configuration in RUN

Reparameterization possible in RUN	Yes
------------------------------------	-----

### Supply voltage

24 V DC	Yes
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
External protection for supply cables (recommendation)	24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic

### Input current

Current consumption, max.	35 mA
---------------------------	-------

### Output voltage

#### Power supply to the transmitters

present	Yes
Rated value (DC)	24 V
short-circuit proof	Yes

Power losses	
Power loss, typ.	0.75 W ; Without encoder supply voltage
Analog inputs	
Number of analog inputs	4
permissible input frequency for current input (destruction limit), max.	30 V
permissible input voltage for voltage input (destruction limit), max.	30 V
Technical unit for temperature measurement adjustable	Yes
Input ranges	
Voltage	Yes
Thermocouple	Yes
Resistance thermometer	Yes
Resistance	Yes
Input ranges (rated values), thermoelements	
Type TXK/TXK(L) to GOST	Yes
Input resistance (Type TXK/TXK(L) to GOST)	1 M $\Omega$
Connection of signal encoders	
for voltage measurement	Yes
Thermocouple (TC)	
Characteristic linearization	
Parameterizable	Yes
Temperature compensation	
Parameterizable	Yes
internal temperature compensation	Yes
external temperature compensation with compensations socket	Yes
Compensation for 0 °C reference point temperature	Yes
Resistance thermometer (RTD)	
Characteristic linearization	
Parameterizable	Yes
Analog value creation	
Measurement principle	integrating (Sigma-Delta)

Integrations and conversion time/ resolution per channel	
Resolution with overrange (bit including sign), max.	16 bit
Integration time, parameterizable	Yes
Interference voltage suppression for interference frequency f1 in Hz	16.67 Hz, 50 Hz, 60 Hz
Smoothing of measured values	
Parameterizable	Yes
Step: None	Yes
Step: low	Yes
Step: Medium	Yes
Step: High	Yes
Errors/accuracies	
cold connection point	+/- 2.5 K
Crosstalk between the inputs, min.	50 dB
Interference voltage suppression for $f = n \times (f_l \pm 1\%)$ , $f_l$ = interference frequency	
Series mode interference (peak value of interference < rated value of input range), min.	70 dB
common mode voltage, max.	10 V
Common mode interference, min.	90 dB
Interrupts/diagnostics/status information	
Alarms	
Alarms	Yes
Diagnostic messages	
Diagnostic functions	Yes ; channel by channel, parameterizable
Monitoring the supply voltage	Yes
Wire break	Yes
Group error	Yes
Diagnostics indication LED	
for status of the inputs	Yes
For voltage monitoring	Yes
for short-circuit	Yes ; Group error (red)
Galvanic isolation	
Galvanic isolation analog inputs	

between the channels	No
between the channels and the backplane bus	Yes
between the channels and the power supply of the electronics	Yes
Permissible potential difference	
between the inputs (UCM)	10 V DC
EMC	
Interference immunity against discharge of static electricity	
Interference immunity against discharge of static electricity acc. to IEC 61000-4-2	Yes
Degree of sharpness	3
Test voltage at air discharge	8 kV
Test voltage at contact discharge	6 kV
Interference immunity to cable-borne interference	
on the supply lines acc. to IEC 61000-4-4	Yes
Interference immunity on signal lines acc. to IEC 61000-4-4	Yes
Interference immunity on supply cables	
Degree of sharpness	3
Test voltage	2 kV
Interference immunity on signal cables >30m	
Degree of sharpness	3
Test voltage	2 kV
Interference immunity on signal cables < 30m	
Degree of sharpness	3
Test voltage	1 kV
Surge immunity	
on the supply lines acc. to IEC 61000-4-5	Yes ; With upstream protective element
Asymmetric interference	
Degree of sharpness	3
Test voltage on supply cables	2 kV
Test voltage on signal cables >30m	2 kV
Immunity against high-frequency electromagnetic fields	

Interference immunity against high-frequency radiation acc. to IEC 61000-4-3	Yes
Degree of sharpness	3
Frequency range of the HF irradiation	80 to 1000 MHz and 1.4 to 2 GHz with 10 V/m; 2.0 GHz to 2.7 GHz with 1 V/m
Electrical field strength at 80% amplitude modulation with 1kHz in the range of 80 MHz to 1000 MHz	10 V/m
Immunity against conducted interference induced by high-frequency fields	
Interference immunity against high frequency current feed acc. to IEC 61000-4-6	Yes
Interference immunity against high-frequency radiation acc. to IEC 61000-4-6	Yes
Degree of sharpness	3
Field strength at 80% amplitude modulation with 1kHz in the range 9 kHz to 80 MHz	10 V
Emission of radio interference acc. to EN 55 011	
Emission of radio interferences acc. to EN 55 011 (limit class A)	Yes
Limit class A, for use in industrial areas	Yes
Emission of radio interference acc. to EN 55 022	
Interference emission acc. to EN 55022, class A	Yes
Emission of conducted and non-conducted interference	
Interference emission from electromagnetic fields	
Limit value in the frequency range 29 MHz to 230 MHz	40 dB (μV/m)
Limit value in the frequency range 230 MHz to 1000 MHz	47 dB (μV/m)
Degree and class of protection	
IP20	Yes
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes ; Included in cULus
C-TICK	Yes
FM approval	Yes
Marine approval	Yes

Climatic and mechanical conditions for storage and transport	
Conditions of use in storage and transport	
Compliance with requirements for storage and transport conditions according to IEC 61131-2	Yes
Climatic conditions for storage and transport	
Free fall	
Drop height, max. (in packaging)	1 m
Temperature	
Permissible temperature range	-40 °C to +70 °C
Min.	-40 °C
max.	70 °C
Air pressure acc. to IEC 60068-2-13	
Min.	660 hPa
max.	1080 hPa
Min.	-1000 m
max.	3500 m
Mechanical conditions for storage and transport	
Constant amplitude at 5 Hz to 9 Hz, max.	3.5 mm
Constant acceleration at 9 Hz to 150 Hz, max	9.8 m/s <sup>2</sup>
Shock (acc. to IEC 60068-2-29)	
Acceleration at a duration of 6 ms per shock (tested with 1000 shocks)	250 m/s <sup>2</sup>
Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	
Min.	0 °C
max.	60 °C
Permissible temperature change	10 °C/h
Air pressure acc. to IEC 60068-2-13	
Min.	795 hPa
max.	1080 hPa
Min.	-1000 m
max.	2000 m
Relative humidity	

Relative humidity at 25 °C, max. (without condensation)	95 %
Pollutant concentrations	
SO2 at RH < 60% without condensation	0.00005 % ; SO2: < 0.5 ppm; RH < 60% condensation-free
H2S at RH < 60% without condensation	0.00001 % ; H2S: < 0.1 ppm; RH < 60% condensation-free
Mechanical conditions in operation	
Vibration (acc. to IEC 60068-2-6)	
Constant amplitude at 10 Hz to 58 Hz, max.	0.35 mm
Dimensions	
Width	15 mm
Weight	
Weight, approx.	30 g
Status	May 26, 2012