

TECHNICAL DATA SHEET



PRODUCT NAME

blackbolt® Zink Spray

PRODUCT NUMBER

3356985112

PRODUCT DESCRIPTION

Repair and maintenance of galvanised and hot dip galvanised surfaces. Used for galvanisation protection of iron inside and out, where the zinc corrodes before the iron. Protects effectively with two applications.

PROPERTIES

Repair and maintenance of galvanised and hot dip galvanized surfaces

DIRECTIONS FOR USE

The undercoat must be dry, clean and free of grease, oil and the like. Shake the can well for at least 1 minute before use. Repeat shaking during use. The spraying distance from the article should be about 25-30 cm. Protects effectively with two applications.

MARKINGS/SAFETY

Extremely flammable aerosol. Causes skin irritation. Very toxic to aquatic life with long lasting effects. Pressurised container: May burst if heated. If medical advice is needed, have product container or label at hand. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. IF ON SKIN: Wash with plenty of soap and water. This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container to an approved waste disposal plant. **Keep out of reach of children.**



Danger!

PR number	-
Net	395 g.
Volumen	500 ml.
Propellant	Butane/Propane gas

Shelf life	Three years from date of manufacture. The product can be used for up to six years after the date of production, provided there is sufficient spray pressure to allow it to be applied to the surface in a satisfactory manner.
------------	--