



Tork Aftøringsklud Sensitiv, Turkis

Farve: Turkis



Fordel

- Allround – klarer de fleste rengøringsopgaver
- Lavt fnuggende
- Fungerer godt sammen med opløsnings- og rengøringsmidler
- Godkendt til kontakt med fødevarer



500



180 m



27.5 cm



1

Produktspecifikation

Artikel	System	Rullelængde	Rullebredde	Rullediameter	Antal ark	Indvendig kerediameter	Lag	Farve
190494	W1 - Aftøringspapir væg-/gulv-/standardsystem, W2 - Aftøringspapir kombirullesystem, W3 - Aftøringspapir pakkesystem	180 m	27.5 cm	25.2 cm	500	70 cm	1	Turkis

Beskrivelse

En lavt fnuggende, fleksibel og smidig klud, der fungerer godt sammen med opløsningsmidler, rengøringsmidler og desinfektionsmidler.



Tork Aftøringsklud Sensitiv, Turkis

Farve: Turkis

Forsendelsesdata

Forbrugerenhed

EAN	7322540741186
Stk.	1
Højde	295 mm
Bredde	264 mm
Længde	264 mm
Volumen	20.6 dm3
Nettovægt	3366 g
Bruttovægt	3673 g

Transportenhed

EAN	7322540741186
Stk.	1
Forbrugerenheder	1
Materiale	Carton
Højde	295 mm
Bredde	264 mm
Længde	264 mm
Volumen	20.6 dm3
Nettovægt	3.37 kg
Bruttovægt	3.67 kg

Palle

EAN	7322540754575
Stk.	72
Forbrugerenheder	72
Højde	1920 mm
Bredde	800 mm
Længde	1200 mm
Volumen	1.5 m3
Nettovægt	242.35 kg
Bruttovægt	264.46 kg



Miljø

Content

Chemical pulp

Polyester

Chemicals

Material

Chemical pulp

Chemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities.

There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free).

ECF is based on oxygen, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone.

Polyester

Polyester fibre is produced from terephthalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length.

Chemicals

Both functional and process chemicals are used. The functional chemical used is wet strength agent. The wet strength agent is a Polyaminopolyamide-epichlorohydrin with a very high affinity to the fibre.

Process chemical used is a surfactant.

Production

This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

Food Contact

This product fulfils the legislative requirements for Food Contact materials, confirmed by external certification performed by ISEGA. The product is safe for wiping food contact surfaces and may also come occasionally into



Tork Aftørringsklud Sensitiv, Turkis

Farve: Turkis

contact with foodstuffs for a short period of time

Disposing / destruction of used product

This product is mainly used for industrial processes and might through use be contaminated with different substances.

This will determine how the used product will be handled / disposed of / destructed. The product itself is suitable for incineration. Contact local authorities before destruction.