

Data sheet for SIMOTICS S-1FK2



Figure similar

MLFB-Ordering data

1FK2206-4AF11-0MA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Basic motor data		Mechanical data	
Motor type	Permanent-magnet synchronous motor, Natural cooling, IP65	Design acc. to Code I	IM B5 (IM V1, IM V3)
Motor type	Compact	Vibration severity grade	Grade A
Static torque	12.00 Nm	Shaft height	63
Static current	7.9 A	Flange size (AB)	125 mm
Maximum torque	36.00 Nm	Centering ring (N)	110 mm
Maximum current	29.5 A	Hole circle (M)	130 mm
Maximum speed	5800 rpm	Screw-on hole (S)	9.0 mm
Rotor moment of inertia	16.800 kgcm ²	Overall length (LB)	244 mm
Weight	10.6 kg	Diameter of shaft (D)	24 mm
		Length of shaft (E)	50 mm
		Length of flange diagonal (P)	158 mm
		Shaft extension	Plain shaft

Rated data

SINAMICS S210, 3AC 400V

Rated speed	3000 rpm
Rated torque	9.10 Nm
Rated current	6.2 A
Rated power	2.85 kW

Encoder system

Encoder system	Encoder AM22DQC: Absolute encoder 22 bit + 12 bit multiturn
----------------	---

Motor connection

Connection type	OCC for S210
Connector size	M23




Figure similar

1FK2206-4AF11-0MA0

Figure similar

¹⁾ Up to three consecutive emergency stops and up to 25% of all emergency stops as a Wmax high energy stop possible.