

## RSE2724 - Vinyl opmærkningstape

|                           |                                                                                                                                                                            |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>        | Enkeltklæbende PVC gulvopmærkningstape med gummibaseret klæber                                                                                                             |
| <b>Product properties</b> | Kraftig, blød PVC-film med mat overflade. Har god vedhæftning til de fleste overflader. Flammeresistent. God mekanisk styrke og let formbar. Modstandsdygtig overfor fugt. |
| <b>Specifications</b>     | Opfylder 2000/53EC direktivet om tilsætning af tungmetaller. Indeholder ikke bly, Crom6, Cadmium eller kviksølv.                                                           |
| <b>Applications</b>       | Anvendes som opmærkningstape på gulve i indendørs miljøer.<br>Kan med fordel bruges sammen med speciel applikator til montering.                                           |
| <b>Storage and ageing</b> | Overfladen, hvor tapen monteres, skal være ren, tør og fri for fedt og olie. Emnerne skal, så vidt muligt have samme temperatur.                                           |
| <b>Applying tips</b>      | Holdbarhed min. 2 år ved 21°C, 50% luftfugtighed og ikke i direkte sollys.                                                                                                 |

### TECHNICAL DATA

|                                    |                         |               |
|------------------------------------|-------------------------|---------------|
| <b>Carrier</b>                     | PVC/film                |               |
| <b>Adhesive</b>                    | Rubber synthetic        |               |
| <b>Colour</b>                      | Black/Yellow, Red/White |               |
| <b>Thickness Total</b>             | 0,16 mm                 | 6,3 Mils      |
| <b>Adhesion on stainless steel</b> | 5 N/25mm                | 1,14 Lbs/inch |
| <b>Tensile strength length</b>     | 63 N/25mm               | 14,4 Lbs/inch |
| <b>Elongation length</b>           | 150 %                   |               |

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

**Stokvis Tapes (UK) Ltd**  
Unit 8, Tring Industrial Estate  
Icknield Way, Tring, Hertfordshire  
tel +44 (0)14 42 82 17 00  
fax +44 (0)14 42 82 17 22  
www.stokvistapes.co.uk  
info@stokvistapes.co.uk