

Data sheet for SIMOTICS S-1FK7




Figure similar

MLFB-Ordering data 1FK7022-5AK71-1VH3

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Physical constants	
Rated speed	6000 rpm	Torque constant	0.46 Nm/A
Number of poles	6	Voltage constant at 20° C	29.0 V/1000*min ⁻¹
Rated torque (100 K)	0.6 Nm	Winding resistance at 20° C	4.20 Ω
Rated current	1.4 A	Rotating field inductance	9.1 mH
Static torque (60 K)	0.70 Nm	Electrical time constant	2.20 ms
Static torque (100 K)	0.8 Nm	Mechanical time constant	1.70 ms
Stall current (60 K)	1.5 A	Thermal time constant	18 min
Stall current (100 K)	1.8 A	Shaft torsional stiffness	3000 Nm/rad
Rotor moment of inertia	0.350 kgcm ²	Net weight of the motor	2.0 kg
Efficiency	86.0 %		

Mechanical data			
Motor type	Compact	Electrical connectors	Connectors for signals and power rotatable
Shaft height	28	Color of the housing	Standard painting (Anthracite RAL 7016)
Cooling	Natural cooling	Holding brake	with holding brake
Radial runout tolerance	0.035 mm	Shaft extension	Plain shaft
Concentricity tolerance	0.08 mm	Encoder system	Encoder AM15DQ: absolute encoder 15 bits (resolution 32768, encoder-internal 16 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Axial runout tolerance	0.08 mm		
Vibration severity grade	Grade A		
Connector size	1		
Degree of protection	IP64		
Design acc. to Code I	IM B5 (IM V1, IM V3)		
Temperature monitoring	KTY84 temperature sensor in the stator winding		




Figure similar

MLFB-Ordering data 1FK7022-5AK71-1VH3

Optimum operating point		Recommended Motor Module	
Optimum speed	6000 rpm	Rated inverter current	3 A
Optimum power	0.4 kW	Maximum inverter current	6 A
Limiting data		Maximum torque	2.75 Nm
Max. permissible speed (mech.)	10000 rpm		