

Command Cable UL (LiYY-TP)

Style 2464, 300 V, 80°C



Technical data

- Special PVC command cable approved to UL Style 2464, cores acc. to UL Style 1061/1729
- **Temperature range**
flexing -10°C to +80°C
fixed installation -20°C to +80°C
- **Nominal voltage**
300 V
- **Test voltage**
1500 V
- **Breakdown voltage**
min. 3000 V
- **Insulation resistance**
min. 100 MOhm x km
- **Minimum bending radius**
flexing 15x cable Ø
fixed installation 7,5x cable Ø

Cable structure

- Tinned copper conductor, fine wire, acc. to ASTM-B 174-95 class J-M
Conductor make-up to:
0,14 mm² = 7x0,162 mm
0,23 mm² = 7x0,202 mm
0,34 mm² = 7x0,254 mm
0,56 mm² = 7x0,32 mm
- Core insulation of special PVC class 43 respectively semirigid acc. to UL Std.1581 tab.50.182 and 50183
- Core identification (pair) to DIN 47100, with colour repetition from pair no. 23 or international colour code
- Cores stranded in pairs with optimal lay length
- Pairs stranded in layers with optimal lay length
- Separator-foil
- Outer sheath of special PVC class 43 acc. to UL Std.1581 tab.50.182
- Sheath colour:
black (international colour code)
grey (DIN 47100 - preferred type)

Properties

- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers
- **To a large extent resistant to**
Oil
Solvents
Acids
Lyes

Tests

- PVC flame retardant acc. to UL VW-1, CSA FT1

Note

- AWG sizes are approximate equivalent values. The actual cross section is in mm².
- Screened analogue type:
command cable UL (LiCY-TP)

Application

Twisted pair control cable for use in tool making machinery conveyor system and production lines, in industrial plants and in air conditioning as well as in the steel producing industries.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no. Sheath colour	No.pairs x cross-sec. mm ²	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
grey					
83904	1 x 2 x 0,14	26	3,6	2,7	20,0
83905	2 x 2 x 0,14	26	5,1	5,4	24,0
83906	3 x 2 x 0,14	26	5,3	8,1	30,0
83907	4 x 2 x 0,14	26	5,8	10,8	38,0
83908	5 x 2 x 0,14	26	6,2	13,6	44,0
83909	6 x 2 x 0,14	26	6,8	16,2	51,0
83910	7 x 2 x 0,14	26	6,8	19,0	57,0
83911	8 x 2 x 0,14	26	7,3	21,7	64,0
83912	10 x 2 x 0,14	26	7,4	26,7	76,0
83913	12 x 2 x 0,14	26	9,1	32,6	93,0
83914	14 x 2 x 0,14	26	9,8	37,4	103,0
83915	15 x 2 x 0,14	26	10,6	40,7	109,0
83916	16 x 2 x 0,14	26	10,6	43,4	112,0
83917	18 x 2 x 0,14	26	11,1	48,5	119,0
83918	20 x 2 x 0,14	26	11,9	54,2	130,0
83919	22 x 2 x 0,14	26	12,4	59,3	150,0
83920	24 x 2 x 0,14	26	13,1	64,7	169,0
83921	25 x 2 x 0,14	26	13,4	67,2	178,0
83922	1 x 2 x 0,23	24	3,8	4,8	32,0
83923	2 x 2 x 0,23	24	5,3	9,7	36,0
83924	3 x 2 x 0,23	24	5,7	14,7	48,0
83925	4 x 2 x 0,23	24	6,2	19,6	56,0
83926	5 x 2 x 0,23	24	6,6	24,6	71,0
83927	6 x 2 x 0,23	24	7,2	29,3	80,0
83928	7 x 2 x 0,23	24	7,2	34,1	89,0
83929	8 x 2 x 0,23	24	7,8	39,1	98,0
83930	10 x 2 x 0,23	24	9,2	48,9	111,0
83931	12 x 2 x 0,23	24	9,7	59,4	135,0
83932	14 x 2 x 0,23	24	10,2	68,7	160,0

Part no. Sheath colour	No.pairs x cross-sec. mm ²	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
black					
65214	1 x 2 x 0,14	26	3,6	2,7	20,0
65215	2 x 2 x 0,14	26	5,1	5,4	24,0
65216	3 x 2 x 0,14	26	5,3	8,1	30,0
65217	4 x 2 x 0,14	26	5,8	10,8	38,0
65218	5 x 2 x 0,14	26	6,2	13,6	44,0
65219	6 x 2 x 0,14	26	6,8	16,2	51,0
65220	7 x 2 x 0,14	26	6,8	19,0	57,0
65221	8 x 2 x 0,14	26	7,3	21,7	64,0
65222	10 x 2 x 0,14	26	7,4	26,7	76,0
65223	12 x 2 x 0,14	26	9,1	32,6	93,0
65224	14 x 2 x 0,14	26	9,8	37,4	103,0
65225	15 x 2 x 0,14	26	10,6	40,7	109,0
65226	16 x 2 x 0,14	26	10,6	43,4	112,0
65227	18 x 2 x 0,14	26	11,1	48,5	119,0
65228	20 x 2 x 0,14	26	11,9	54,2	130,0
65229	22 x 2 x 0,14	26	12,4	59,3	150,0
65230	24 x 2 x 0,14	26	13,1	64,7	169,0
65231	25 x 2 x 0,14	26	13,4	67,2	178,0
65232	1 x 2 x 0,23	24	3,8	4,8	32,0
65233	2 x 2 x 0,23	24	5,3	9,7	36,0
65234	3 x 2 x 0,23	24	5,7	14,7	48,0
65235	4 x 2 x 0,23	24	6,2	19,6	56,0
65236	5 x 2 x 0,23	24	6,6	24,6	71,0
65237	6 x 2 x 0,23	24	7,2	29,3	80,0
65238	7 x 2 x 0,23	24	7,2	34,1	89,0
65239	8 x 2 x 0,23	24	7,8	39,1	98,0
65240	10 x 2 x 0,23	24	9,2	48,9	111,0
65241	12 x 2 x 0,23	24	9,7	59,4	135,0
65242	14 x 2 x 0,23	24	10,2	68,7	160,0

Continuation ►

Command Cable UL (LiYY-TP)

Style 2464, 300 V, 80°C



Part no. Sheath colour grey	No.pairs x cross-sec. mm ²	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
83933	15 x 2 x 0,23	24	10,9	73,7	171,0
83934	16 x 2 x 0,23	24	10,9	79,1	185,0
83935	18 x 2 x 0,23	24	11,5	88,9	209,0
83936	20 x 2 x 0,23	24	12,2	98,4	230,0
83937	22 x 2 x 0,23	24	13,0	108,6	248,0
83938	24 x 2 x 0,23	24	13,7	117,9	279,0
83939	25 x 2 x 0,23	24	14,2	123,5	292,0
83940	1 x 2 x 0,34	22	4,2	6,5	38,0
83941	2 x 2 x 0,34	22	5,9	13,0	44,0
83942	3 x 2 x 0,34	22	6,3	19,5	60,0
83943	4 x 2 x 0,34	22	7,0	26,1	79,0
83944	5 x 2 x 0,34	22	7,6	32,6	92,0
83945	6 x 2 x 0,34	22	8,2	39,2	119,0
83946	7 x 2 x 0,34	22	8,2	45,7	128,0
83947	8 x 2 x 0,34	22	9,0	52,3	139,0
83948	10 x 2 x 0,34	22	10,7	65,3	171,0
83949	12 x 2 x 0,34	22	11,3	78,4	194,0
83950	14 x 2 x 0,34	22	12,1	91,5	222,0
83951	15 x 2 x 0,34	22	12,7	97,8	231,0
83952	16 x 2 x 0,34	22	12,7	104,6	240,0
83953	18 x 2 x 0,34	22	13,6	117,8	264,0
83954	20 x 2 x 0,34	22	14,4	130,7	291,0
83955	22 x 2 x 0,34	22	15,1	143,6	300,0
83956	24 x 2 x 0,34	22	16,2	156,8	359,0
83957	25 x 2 x 0,34	22	16,7	163,3	381,0
83958	1 x 2 x 0,56	20	4,6	10,8	60,0
83959	2 x 2 x 0,56	20	6,5	21,5	80,0
83960	3 x 2 x 0,56	20	7,1	32,3	94,0
83961	4 x 2 x 0,56	20	7,8	43,1	104,0
83962	5 x 2 x 0,56	20	8,6	53,8	130,0
83963	6 x 2 x 0,56	20	9,6	64,6	151,0
83964	7 x 2 x 0,56	20	9,6	75,3	174,0
83965	8 x 2 x 0,56	20	12,2	86,1	262,0
83966	10 x 2 x 0,56	20	12,5	107,7	298,0
83967	12 x 2 x 0,56	20	13,1	129,1	302,0
83968	14 x 2 x 0,56	20	13,8	150,6	327,0
83969	15 x 2 x 0,56	20	14,7	161,3	370,0
83970	16 x 2 x 0,56	20	14,7	172,1	402,0
83971	18 x 2 x 0,56	20	15,7	193,6	480,0
83972	20 x 2 x 0,56	20	16,7	215,1	551,0
83973	22 x 2 x 0,56	20	17,2	236,6	621,0
83974	24 x 2 x 0,56	20	18,6	258,0	703,0
83975	25 x 2 x 0,56	20	19,2	268,9	721,0

Part no. Sheath colour black	No.pairs x cross-sec. mm ²	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
65243	15 x 2 x 0,23	24	10,9	73,7	171,0
65244	16 x 2 x 0,23	24	10,9	79,1	185,0
65245	18 x 2 x 0,23	24	11,5	88,9	209,0
65246	20 x 2 x 0,23	24	12,2	98,4	230,0
65247	22 x 2 x 0,23	24	13,0	108,6	248,0
65248	24 x 2 x 0,23	24	13,7	117,9	279,0
65249	25 x 2 x 0,23	24	14,2	123,5	292,0
65250	1 x 2 x 0,34	22	4,2	6,5	38,0
65251	2 x 2 x 0,34	22	5,9	13,0	44,0
65252	3 x 2 x 0,34	22	6,3	19,5	60,0
65253	4 x 2 x 0,34	22	7,0	26,1	79,0
65254	5 x 2 x 0,34	22	7,6	32,6	92,0
65255	6 x 2 x 0,34	22	8,2	39,2	119,0
65256	7 x 2 x 0,34	22	8,2	45,7	128,0
65257	8 x 2 x 0,34	22	9,0	52,3	139,0
65258	10 x 2 x 0,34	22	10,7	65,3	171,0
65259	12 x 2 x 0,34	22	11,3	78,4	194,0
65260	14 x 2 x 0,34	22	12,1	91,5	222,0
65261	15 x 2 x 0,34	22	12,7	97,8	231,0
65262	16 x 2 x 0,34	22	12,7	104,6	240,0
65263	18 x 2 x 0,34	22	13,6	117,8	264,0
65264	20 x 2 x 0,34	22	14,4	130,7	291,0
65265	22 x 2 x 0,34	22	15,1	143,6	300,0
65266	24 x 2 x 0,34	22	16,2	156,8	359,0
65267	25 x 2 x 0,34	22	16,7	163,3	381,0
65268	1 x 2 x 0,56	20	4,6	10,8	60,0
65269	2 x 2 x 0,56	20	6,5	21,5	80,0
65270	3 x 2 x 0,56	20	7,1	32,3	94,0
65271	4 x 2 x 0,56	20	7,8	43,1	104,0
65272	5 x 2 x 0,56	20	8,6	53,8	130,0
65273	6 x 2 x 0,56	20	9,6	64,6	151,0
65274	7 x 2 x 0,56	20	9,6	75,3	174,0
65275	8 x 2 x 0,56	20	12,1	86,1	262,0
65276	10 x 2 x 0,56	20	12,5	107,7	298,0
65277	12 x 2 x 0,56	20	13,1	129,1	302,0
65278	14 x 2 x 0,56	20	13,8	150,6	327,0
65279	15 x 2 x 0,56	20	14,7	161,3	370,0
65280	16 x 2 x 0,56	20	14,7	172,1	402,0
65281	18 x 2 x 0,56	20	15,7	193,6	480,0
65282	20 x 2 x 0,56	20	16,7	215,1	551,0
65283	22 x 2 x 0,56	20	17,2	236,6	621,0
65284	24 x 2 x 0,56	20	18,6	258,0	703,0
65285	25 x 2 x 0,56	20	19,2	268,9	721,0

Dimensions and specifications may be changed without prior notice. (RN02)