### **ROLLGLISS RESCUE KIT: AG625010XX**





# THE ROLLGLISS REMOTE RESCUE KIT: SIMPLE, FAST, PRACTICAL.

Being protected against falls from height is a good thing, but having a rescue method that is simple, fast and practical is even better!

- Universal solution for the rescue of a worker remaining suspended after a fall.
- Simple: you do not have to be a rescue specialist to use it.
- Fast: on average, a rescue takes 6 minutes.
- Practical: everything is contained in a backpack with a total weight of 8 kg.
- Flexible: the kit is available in different versions with varying rope lengths of 10, 20 and 30m.



## **ROLLGLISS RESCUE KIT: AG625010XX**



Immediate Worker Assistance. Someone who remains suspended after a fall risks serious injuries linked to his/her static suspended position, and these can lead to death after a few hours. The portable Rollgliss Rescue Kit is a universal solution and ideal for maintenance work and use on building sites or by groups of people working at height.

Ease of use. The Rollgliss Rescue Kit can be used by anyone who is working at height and does not require any particular rescue skills. You simply find an anchorage point on the structure that is at a maximum of 4.5 m from the person to be rescued.

The kit contains a small number of pre-assembled pieces and rescues can be completed in a few simple steps:

- Installation of the system.
- Connection to the worker using the telescopic rod.
- Gentle elevation of the worker using the rigging system.
- Disconnection of the worker and controlled dencent.



### **Main Components**



# **Rollgliss Rescue Kit Components**

- 1. Main rope: in 11 mm nylon.
- 2. Recovery Hook: aluminium, 60 mm gate.
- **3. R250 Descender:** with anti-panic handle that blocks with the handle is moved to its full extent in either direction.
- 4. Telescopic Rod: 5 m.
- 5. Anchorage Rig with Protection System.
- 6. Rigging System: ability to raise worker and disconnect the fall-arrest equipment.

### Specifications:

- **Usage Limits** Evacuation and rescue of a worker Available in three different rope lengths: maximum 150 kg.
- Total Weight 8 kg.
- Cord High strength, 100% Polyester.
- Rope 11 mm nylon breaking strength > 2200 daN.

**10 meters** - AG62501010

**20 meters** - AG62501020

30 meters - AG62501030

