

# TUBIS BL

## Incl. TW

3x1,5mm² through-wiring  
ex factory

## Aluminium

Aluminium carrier for  
optimal thermal management

## Noble

Stainless steel clamps

**HOUSING** Tube and end caps made of PMMA

**ELECTRICAL COMPONENTS** High power LED, LED converter.

**ASSEMBLY** Variable mounting distances by PRACHT-CLAMP-SYSTEM. Suitable for ceiling, wall, pendant and rail mounting.

**FIELDS OF APPLICATION** Washing plants, wet rooms, workshops, unprotected outdoor areas, agriculture (unlimited), acid and alkaline cleaning, plants and oily environments.

**CONFIGURABILITY** Possible in the TUBIS PRO LINE. E.g.: additional resistances, light colors, control module, emergency lighting modules and a lot more.

Individual luminaire, color temperature 4000 K, Ra>80, diameter 70mm

Power	Light distribution	Luminous flux	P/N	Length	Weight
1x20 W	120° wide	2800 lm	5240024	1330 mm	1,8 kg
1x36 W	120° wide	5400 lm	5240034	1330 mm	1,8 kg
1x24 W	120° wide	3800 lm	5240025	1629 mm	2,2 kg
1x42 W	120° wide	6500 lm	5240035	1629 mm	2,2 kg



Protection class I according to EN 60598  
Protection type IP67/IP69K  
AC/DC 220-240 V 50/60 Hz \*registered

**PRACHT®**

**Fast**

Solid end caps, extremely  
fast connection

**Resistant**

High-quality PMMA round tube  
(IK06, Ø70mm)



# SPECIALIST

**ACID-ALKALI-RESISTANT  
OIL-RESISTANT AGRICULTURE  
STURDY FAST ASSEMBLY ENEC  
FOR UNPROTECTED OUTDOOR AREAS  
TUBULAR LUMINAIRE -20° C ... +40° C**


**3**

YEAR  
WARRANTY



UP TO 100.000 h  
LIFETIME

**IP67  
IP69K**



INCL. TW  
(3X1,5MM²)



UNRESTRICTED  
LIVESTOCK  
FARMING



FROM -20° C  
TO +40° C



UNPROTECTED  
OUTDOOR AREA

PRACHT.COM

+49 64 66 / 91 40 - 0