

SIEMENS

Product data sheet

6GK1900-1LB00-0AC0



FC FO SC PLUG ON-SITE MOUNTING ON FC FO CABLES (62.5/200/230) PACKAGE: 20 PCS. SC PLUGS +10 PCS. DUPLEX CLIP + CLEANING CLOTHS

[nicht versorgt: PMD_ABS675_001_000]

-
-
-
-

10 Mbit/s
100 Mbit/s
1000 Mbit/s
9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of optical interfaces / for optical waveguide	1
Design of the electrical connection / [nicht versorgt - FastConnect]	Yes

Design, dimensions and weight

Width	8 mm
Height	8 mm
Depth	49 mm
Net weight	11 g

Permitted ambient conditions

Ambient temperature	
• during operating	-40 °C ... 85 °C

• during storage	-40 °C ... 85 °C
• during transport	-40 °C ... 85 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP20
Product properties, functions, components / general	
Product feature / [not supplied - silicon-free]	Yes
Composant produit	
• décharge de traction	Yes
Standards, specifications, approvals	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	No
letzte Änderung:	Nov 21, 2011