



Maschinenleuchte 23 Watt LED 220-240 Volt

Artikelnummer: 3202330-15-V2



Image similar

Machine light 23 Watt with SMD LEDs

Length: 680 mm diameter 67 mm

Driver 220-240 Volt AC 50-60 Hz and LED-unit with diffuse cover

Light output: approx. 2204 lm = 2824 Lux on 0,5 m

Angle of reflected beam: 120°, colour temperature: 4000 K

Protection tube CAB (Cellulose Aceto Butyrat) clear

Through-wired with blind plug

Two holders H5

Temperature: - 25° / + 40°C

Average life of light source: 40000 hours

Protection class I, energy class A+, IP67, D,

TÜV, ENEC 24, CB Prüfung

RoHS, WEEE, CE

Packing unit: max. 4 pieces per box

SKU	3202330-15-V2
Light source base	N/A
Colour temperature (Kelvin)	4.000
Light source wattage (w)	23
Type of ballast	Driver
Frequency spectrum (Hertz)	50-60
Length (mm)	680
Height of light	keine Angabe
Length of light area (mm)	keine Angabe
Material of protection tube	Kunststoff (CAB)
Reduced glare effect	Yes
External diameter of protection tube (mm)	63
Ball joint	No
Quantity of sockets	Without
Type of plug	N/A
Position of ballast	Internal
Vorschaltgerät	Driver EVG 220-240V 50-60Hz
Cover	CAB 63 klar u. dif. Abd.

Type of light source	SMD LED
Luminous efficiency (Lumen)	2.204
Angle of reflected beam	120
Total power (Watt)	23
Voltage (Volt)	220-240
Type of current AC / DC	AC
Lamp width	keine Angabe
Light diameter	68
Height of light area	keine Angabe
Chemical resistance	Yes
Wall thickness cover (mm)	3
Linkage	Without linkage
Pivoted joint	No
Magnetic base	No
Length of cable (mm)	keine Angabe
Through-wired for serial installation	Possible
Reparable	Yes
Incl. standard holders	Yes
Connection voltage	230 Volt
Diameter	Normal (67 mm)

Impact resistance	Yes	Driver/Ballast	Electronic ballast (EVG)
Light source diameter	keine Angabe	Light source length	610

Rohrlux GmbH • Mühlenweg 3 • D- 26789 Leer • Tel.: +49 491 97883-0 • Fax:+49 491 97883 50

Produktänderungen, technische Änderungen und Irrtümer vorbehalten.

Product changes, technical changes and mistakes reserved.

Rohrlux GmbH 16.07.20