

Product data sheet for uvex rubiflex NB60S



Due to the cotton interlock supporting material, the uvex rubiflex S NB60S chemical protection glove is suitable for many applications where protection against chemicals as well as increased mechanical protection are required.

Characteristics

- Ergonomic fit
- Good grip
- Very good tactile feel

Material number	89647
Sizes	8 - 11
Standard	EN 420:2003 + A1:2009, EN 388:2016, EN ISO 374-1:2016
Test chemicals	n-Heptane (J), Sodium hydroxide 40% (K), Ammonia water 25% (O), Hydrogen peroxide 30% (P), Formaldehyde 37% (T)

EN ISO 374-1:2016 / Type B



JK OPT

EN 388:2016



2 1 2 1 X



MADE IN GERMANY

Manufacturer address

UVEX SAFETY Gloves GmbH & Co. KG
Elso-Klöver-Str. 6
D-21337 Lüneburg
uvex-safety.de

Performance class in accordance with EN 388	2 1 2 1 X
Performance class in accordance with EN 407	X 1 X X X X
Outer material	Cotton interlock
Coating	Nitrile rubber (NBR)
Coating surface area	Fully coated
Coating thickness	0.50 mm
Type	With gauntlet
Colour	Green
Glove length	60 cm