

STEADY-LIGHT ELEMENTS, YELLOW 12V - 230V



General technical details:

Product brand name		SIRIUS
product designation		signaling columns element, optical
Product component / fluorescent materials		No
Design of the optical signal		continous light
Type of voltage		
• of the operating voltage		AC/DC
Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating voltage		
• for DC / rated value	V	230 ... 24
• at 50 Hz / at AC / rated value	V	24 ... 230
• at 60 Hz / at AC / rated value	V	24 ... 230
Item designation		
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		H
• according to DIN EN 61346-2		P

Mechanical design:

Color / of the optical signal element		yellow
--	--	--------

External diameter / of the signal column element	mm	50
--	----	----

Lamp:

Nature of fluorescent material	filament lamp / LED
--------------------------------	---------------------

Ambient conditions:

Ambient temperature

- during operating

°C

-20 ... +50

Protection class IP

IP54

Depth

mm

50

Height

mm

55

Width

mm

50

Certificates/approvals:

General Product Approval

Shipping Approval

other

[ROSTEST](#)



[Manufacturer](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WD4200-1AD/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD4200-1AD

last change:

Nov 4, 2011