



CONNECTION ELEMENT WITH COVER FOR MOUNTING
ON PIPES,
FLOOR AND BRACKETS

General technical details:



Product brand name		SIRIUS
product designation		accessories for signaling columns, connection element
Type of voltage • of the operating voltage		AC/DC
Operating frequency • 1 / rated value • 2 / rated value	Hz Hz	50 60
Operating voltage • for DC / rated value • at 50 Hz / at AC / rated value • at 60 Hz / at AC / rated value	V V V	230 ... 24 24 ... 230 24 ... 230
Item designation • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		E X

Mechanical design:

Design of the electrical connection		screw-type terminals
Type of mounting		

• pipe mounting		Yes
• angle mounting		Yes
• floor mounting		Yes
Color / of the housing		black
External diameter / of the signal column element	mm	50

Ambient conditions:		
Ambient temperature		
• during operating	°C	-20 ... +50
Protection class IP		IP54
Depth	mm	53
Height	mm	41.5
Width	mm	53

Certificates/approvals:		
General Product Approval	Shipping Approval	other
ROSTEST	 	Manufacturer

Further information:
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs
Industry Mall (Online ordering system) http://www.siemens.com/industrial-controls/mall
Cax online generator: http://www.siemens.com/cax
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/8WD4208-0AA/all
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD4208-0AA

last change:

Nov 4, 2011