



SIGNALLING COLUMN CONNECT. ELEMENT FOR WITH  
PIPE MOUNTING COVER LID

### General technical details:

<b>Product brand name</b>		SIRIUS
<b>product designation</b>		signaling columns element, connection module
<b>Type of voltage</b> • of the operating voltage		AC/DC
<b>Operating frequency</b> • 1 / rated value • 2 / rated value	Hz Hz	50 60
<b>Operating voltage</b> • for DC / rated value • at 50 Hz / at AC / rated value • at 60 Hz / at AC / rated value	V V V	230 ... 24 24 ... 230 24 ... 230
<b>Item designation</b> • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		E X

### Mechanical design:




<b>Design of the electrical connection</b>		screw-type terminals
<b>Type of mounting</b> • pipe mounting		Yes

• angle mounting		No
• floor mounting		No
<b>Color / of the housing</b>		black
<b>External diameter / of the signal column element</b>	mm	70

#### Ambient conditions:

<b>Ambient temperature</b>		
• during operating	°C	-20 ... 50
<b>Protection class IP</b>		IP65
<b>Depth</b>	mm	40
<b>Height</b>	mm	42
<b>Width</b>	mm	70

#### Certificates/approvals:

General Product Approval	Shipping Approval	other
<a href="#">ROSTEST</a>  UL	 BUREAU VERITAS	 DNV <a href="#">Manufacturer</a>

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

##### Cax online generator:

<http://www.siemens.com/cax>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/VWW/view/en/8WD4408-0AA/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WD4408-0AA](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD4408-0AA)

last change:

Nov 4, 2011