

SIGNALLING COLUMNS,  
ACCESSORIES LED 24V UC, BA 15D, YELLOW



### General technical details:

<b>Product brand name</b>		SIRIUS
<b>product designation</b>		accessories for signaling columns, LED
<b>Type of voltage</b> <ul style="list-style-type: none"> <li>• of the supply voltage</li> <li>• of the fluorescent material</li> </ul>		AC/DC
<b>Supply voltage</b> <ul style="list-style-type: none"> <li>• 1 / of the fluorescent material / at 50 Hz / for AC / rated value</li> <li>• 1 / of the fluorescent material / at 60 Hz / for AC / rated value</li> <li>• 1 / of the fluorescent material / for DC / rated value</li> </ul>	V	24
	V	24
	V	24
<b>Item designation</b> <ul style="list-style-type: none"> <li>• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750</li> <li>• according to DIN EN 61346-2</li> </ul>		H
		P

### Mechanical design:

<b>Color / of the optical signal element</b>		yellow
<b>External diameter / of the signal column element</b>	mm	70

### Ambient conditions:

<b>Protection class IP</b>		IP65
----------------------------	--	------

## Certificates/approvals:

**General Product  
Approval**

[ROSTEST](#)

**Shipping Approval**



**other**

[Manufacturer](#)

## Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

**Cax online generator:**

<http://www.siemens.com/cax>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/8WD4428-6XD/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WD4428-6XD](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD4428-6XD)

**last change:**

Nov 4, 2011