

SIGNALLING COLUMNS,
ACCESSORIES LED 24V UC, BA 15D, RED



General technical details:

Product brand name		SIRIUS
product designation		accessories for signaling columns, LED
Type of voltage <ul style="list-style-type: none"> • of the supply voltage • of the fluorescent material 		AC/DC
Supply voltage <ul style="list-style-type: none"> • 1 / of the fluorescent material / at 50 Hz / for AC / rated value • 1 / of the fluorescent material / at 60 Hz / for AC / rated value • 1 / of the fluorescent material / for DC / rated value 	V	24
	V	24
	V	24
Item designation <ul style="list-style-type: none"> • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2 		H
		P

Mechanical design:

Color / of the optical signal element		red
External diameter / of the signal column element	mm	70

Ambient conditions:

Protection class IP		IP65
----------------------------	--	------

Certificates/approvals:

**General Product
Approval**

[ROSTEST](#)

Shipping Approval



other

[Manufacturer](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WD4428-6XB/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD4428-6XB

last change:

Nov 4, 2011