SIEMENS

Product data sheet 8WD4220-0FA



BUZZER ELEMENT 24V UC (PULSAT./CONTIN. TONE ADJUST.)

General technical details:				
Product brand name		SIRIUS		
product designation		signaling columns element, accoustic		
Type of voltage				
of the supply voltage				
of the acoustic signal element		AC/DC		
Consumed current / for rated value of supply voltage	mA	25		
Supply voltage / 1 / of the acoustic signal element				
• at 50 Hz / for AC / rated value	V	24		
• at 60 Hz / for AC / rated value	V	24		
• for DC / rated value	V	24		
Design of the acoustic signal type		continuous tone / pulse tone		
Loudness level	dB	80		
Item designation				
 according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 		Н		
• according to DIN EN 61346-2		P		

Mechanical design:			
Color / of the housing		black	
External diameter / of the signal column element	mm	50	

Ambient conditions:				
Ambient temperature				
during operating	°C	-20 +50		
Protection class IP		IP54		
Product function / adjustable acoustic signal		Yes		
Depth	mm	50		
Height	mm	75		
Width	mm	50		

Certificates/approvals:

General Product Approval

Shipping Approval

other

ROSTEST







Manufacturer

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

Cax online generator:

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/8WD4220-0FA/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD4220-0FA

last change: Nov 4, 2011