



BUZZER ELEMENT 230V AC (PULSAT./CONTIN. TONE ADJUST.)

General technical details:

Product brand name		SIRIUS
product designation		signaling columns element, accoustic
Type of voltage <ul style="list-style-type: none"> • of the supply voltage • of the acoustic signal element 		AC
Consumed current / for rated value of supply voltage	mA	25
Supply voltage / 1 / of the acoustic signal element <ul style="list-style-type: none"> • at 50 Hz / for AC / rated value • at 60 Hz / for AC / rated value 	V V	230 230
Design of the acoustic signal type		continuous tone / pulse tone
Loudness level	dB	80
Item designation <ul style="list-style-type: none"> • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2 		H P

Mechanical design:

Color / of the housing		black
External diameter / of the signal column element	mm	50

Ambient conditions:

Ambient temperature

- during operating

°C

-20 ... +50

Protection class IP

IP54

Product function / adjustable acoustic signal

Yes

Depth

mm

50

Height

mm

75

Width

mm

50

Certificates/approvals:

General Product Approval

[ROSTEST](#)



Shipping Approval



other

[Manufacturer](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WD4250-0FA/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD4250-0FA

last change:

Nov 4, 2011