

CONNECTION CABLE;
LENGTH 0,025M;
FLAT;
CONNECTION OF BASIC UNIT TO EXPANSION
MODULES VIA SYSTEM INTERFACE

General technical data:

Product brand name		SIRIUS
product designation		connecting cable
Ambient temperature		
• during storage	°C	-40 ... 80
• during operating	°C	-25 ... 60
• during transport	°C	-40 ... 80
Relative humidity		
• during operating phase	%	5 ... 95

Certificates/approvals:

Verification of suitability	CE / UL / CSA / CCC / C-TICK / GOST / NOM / RoHS
------------------------------------	--

General Product Approval



CQC

[ROSTEST](#)

For use in hazardous locations

[CQST](#)

Test Certificates

[Manufacturer](#)

Shipping Approval



ABS



BUREAU
VERITAS



DNV



GL



PRS

other

[Manufacturer](#)

[PNO](#)

[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator


<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3UF7930-0AA00-0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3UF7930-0AA00-0



last change:

Oct 24, 2011