

ADDRESSING PLUG,
FOR ASSIGNING THE PROFIBUS ADDRESS TO A BASIC
UNIT W/O PC/PG TO SIMOCODE PRO W/O PC/PG



General technical data:		
Product brand name		SIRIUS
product designation		addressing plug
Ambient temperature		
• during storage	°C	-40 ... 80
• during operating	°C	-25 ... 60
• during transport	°C	-40 ... 80
Relative humidity		
• during operating phase	%	5 ... 95
Certificates/approvals:		
Verification of suitability		CE / UL / CSA / CCC / C-TICK / GOST / NOM / RoHS

General Product Approval			For use in hazardous locations	Test Certificates
--------------------------	--	--	--------------------------------	-------------------



CQC



CSA

[ROSTEST](#)



UL

[CQST](#)

[Manufacturer](#)

Shipping Approval

other



ABS



DNV



GL

[Manufacturer](#)

[PNO](#)

[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3UF7910-0AA00-0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3UF7910-0AA00-0

last change:

Oct 24, 2011