

PLUG-IN RELAY 2 CHANGEOVER CONT. AC 230V



General technical details:

Supply voltage frequency / for auxiliary and control current circuit / rated value

- minimum
- maximum

Hz
Hz

50
60

type of voltage

AC

Control supply voltage

- at 50 Hz / at AC / rated value
 - minimum
 - maximum
- at 60 Hz / at AC / rated value
 - minimum
 - maximum

V
V
V
V

230
230
230
230

Number of NC contacts

- for auxiliary contacts

0

Number of NO contacts

- for auxiliary contacts

0

Number of change-over switches

- for auxiliary contacts

2

Operating current / of the auxiliary contacts

- at DC-13

• at 24 V	A	8
• at AC-15		
• at 230 V	A	5
Design of the switching function		changeover switch
• guided		No
Switching behaviour		monostable

Mechanical design:

Design of the electrical connection		screw-type terminals
Design of the relay operating mechanism		poled
Product component / jumper socket		No
Width	mm	22.5
Height	mm	28
Depth	mm	35

Certificates/approvals:

General Product Approval

other

[ROSTEST](#)



[Manufacturer](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/LZX:PT270730/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZX:PT270730

last change:

Oct 24, 2011