



PLUG-IN RELAY 1CO RELAY 15MM, 24V DC

General technical details:		
type of voltage		DC
Control supply voltage <ul style="list-style-type: none">• for DC / rated value• minimum• maximum	V V	24 24
Number of NC contacts <ul style="list-style-type: none">• for auxiliary contacts		0
Number of NO contacts <ul style="list-style-type: none">• for auxiliary contacts		0
Number of change-over switches <ul style="list-style-type: none">• for auxiliary contacts		1
Operating current / of the auxiliary contacts <ul style="list-style-type: none">• at AC-15• at 230 V	A	3
Design of the switching function <ul style="list-style-type: none">• guided		changeover switch No
Switching behaviour		monostable
Mechanical design:		
Design of the electrical connection		screw-type terminals

Design of the relay operating mechanism		poled
Product component / jumper socket		No
Width	mm	12.7
Height	mm	12.7
Depth	mm	19.5

Certificates/approvals:

General Product Approval

other

[ROSTEST](#)



[Manufacturer](#)



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/LZX:RT314024/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZX:RT314024

last change:

Oct 24, 2011