## **SIEMENS**

Product data sheet LZX:RT315024



PLUG-IN RELAY 1 CHANGEOVER C.,HARD GOLD PLAT. 24V DC

General technical details:				
type of voltage		DC		
Control supply voltage				
• for DC / rated value				
• minimum	V	24		
• maximum	V	24		
Number of NC contacts				
for auxiliary contacts		0		
Number of NO contacts				
for auxiliary contacts		0		
Number of change-over switches				
• for auxiliary contacts		1		
Operating current / of the auxiliary contacts				
• at AC-15				
• at 230 V	Α	3		
Design of the switching function		changeover switch		
• guided		No		
Switching behaviour		monostable		

Mechanical design:				
Design of the electrical connection		screw-type terminals		

Design of the relay operating mechanism		poled
Product component / jumper socket		No
Width	mm	12.7
Height	mm	12.7
Depth	mm	19.5

## Certificates/approvals:

**General Product Approval** 

other

**ROSTEST** 



Manufacturer

## Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

**CAx-Online-Generator** 

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/LZX:RT315024/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=LZX:RT315024}$ 

last change: Oct 24, 2011