



PLUG-IN RELAY 1 CHANGEOVER C.,HARD GOLD PLAT.  
230V AC

### General technical details:

<b>Supply voltage frequency / for auxiliary and control current circuit / rated value</b>		
• minimum	Hz	50
• maximum	Hz	60
<b>type of voltage</b>		AC
<b>Control supply voltage</b>		
• at 50 Hz / at AC / rated value		
• minimum	V	230
• maximum	V	230
• at 60 Hz / at AC / rated value		
• minimum	V	230
• maximum	V	230
<b>Number of NC contacts</b>		
• for auxiliary contacts		0
<b>Number of NO contacts</b>		
• for auxiliary contacts		0
<b>Number of change-over switches</b>		
• for auxiliary contacts		1
<b>Operating current / of the auxiliary contacts</b>		
• at AC-15		

• at 230 V	A	3
<b>Design of the switching function</b>		changeover switch
• guided		No
<b>Switching behaviour</b>		monostable

#### Mechanical design:

<b>Design of the electrical connection</b>		screw-type terminals
<b>Design of the relay operating mechanism</b>		poled
<b>Product component / jumper socket</b>		No
<b>Width</b>	mm	12.7
<b>Height</b>	mm	12.7
<b>Depth</b>	mm	19.5

#### Certificates/approvals:

General Product Approval

other

[ROSTEST](#)



[Manufacturer](#)

#### Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/LZX:RT315730/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=LZX:RT315730](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZX:RT315730)

**last change:**

Oct 24, 2011