# **SIEMENS**

# Data sheet

## 3SE6605-2BA

Magnet switch Contact block, rectangular large 25 x 88 mm Contact elements 1 NC/1 NO with 3 m cable



Product brand name	SIRIUS			
Product designation	Magnetically operated switch			
Design of the product	Rectangular sensor unit			
Product type designation	3SE66			
Suitability for use safety-related circuits	Yes			
General technical data				
Product function				
<ul> <li>positive opening</li> </ul>	No			
<ul> <li>cross-circuit/short-circuit recognition</li> </ul>	Yes			
Type of voltage of the operating voltage	AC/DC			
Protection class IP	IP67			
Shock resistance				
• acc. to IEC 60068-2-27	Sinusoidal half-wave 30g / 11 ms			
Vibration resistance				
• acc. to IEC 60068-2-6	10 55 Hz: 1 mm			
Reference code acc. to DIN 40719 extended	S			
according to IEC 204-2 acc. to IEC 750				
Type of voltage	AC/DC			
Height of the sensor	13 mm			

Length of the sensor	88 mm
Width of the sensor	25 mm
Material of the active sensor area	plastic
Mechanical installation condition for sensor	no flush installation possible
Operating voltage rated value	100 V
Operating current rated value	400 mA
Operating power rated value	10 W
Number of NC contacts	
	4
• for auxiliary contacts	1
Number of NO contacts	
<ul> <li>for auxiliary contacts</li> </ul>	1
Number of CO contacts for auxiliary contacts	0
Enclosure	
Design of the housing	block
Material of the enclosure	plastic
Material of cable sheath	PVC
Actuator	
Design of the operating mechanism	magnet
Contact	
Circuit principle	reed switches
Switching frequency	5 Hz
Safe operating distance OFF	15 mm
Safe operating distance ON	5 mm
Design of the switching function	NC contact and NO contact
Connections/Terminals	
Type of electrical connection	cable
Wire length	3 m
Safety related data	
Safety Integrity Level (SIL) acc. to IEC 61508	3
Performance level (PL) acc. to EN ISO 13849-1	e
Category acc. to EN 954-1	4
Ambient conditions	
Ambient temperature	
<ul> <li>during operation</li> </ul>	-25 +70 °C
<ul> <li>during storage and transport</li> </ul>	-25 +70 °C
Inputs/ Outputs Type of switching output	Reed contacts
Display	
Evaluation version required	yes

Installation/ mounting/ dimensions						
Mounting type	sc	screw fixing				
Certificates/approvals						
General Product Approval	Functional	other				
	Safety/Safety					
	of Machinery					
💮 ГПГ	Miscellaneous	Confirmation	Miscellaneous			

## Further information

UL

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs

### Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SE6605-2BA

#### Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SE6605-2BA

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3SE6605-2BA

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SE6605-2BA&lang=en

last modified:

11/17/2018