





TWIST LEVER FOR POSITION SWITCH 3SE52
STAINLESS STEEL LEVER 21MM LONG PLASTIC
ROLLER 19MM FOR ACTUATOR HEAD ACC. TO EN
50047

General technical details:

product designation		actuator for part-turn actuator
Mechanical operating cycles as operating time		
• typical		15,000,000
Resistance against vibration		0.35 mm / 5g
Resistance against shock		30g / 11 ms
Ambient temperature		
• during operating	°C	-25 ... +85
• during storage	°C	-40 ... +90
Design of the operating mechanism		stainless steel lever, 21 mm long, straight, plastic roller 19 mm
Built in orientation		any
Item designation		
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		E
• according to DIN EN 61346-2		T

Certificates/approvals:

General Product Approval	Functional Safety / Safety of Machinery	Test Certificates
 CQC	 VDE	 TÜV
 CSA	ROSTEST	Manufacturer
other Manufacturer		

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SE5000-0AA31/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE5000-0AA31

last change:

Nov 28, 2011