





ACTUATOR HEAD FOR POSITION SWITCH 3SE51/52
ROLLER LEVER W. METAL LEVER AND PLASTIC
ROLLER 22MM

General technical details:

product designation		actuator head for position switch
Mechanical operating cycles as operating time • typical		15,000,000
Resistance against vibration		0.35 mm / 5g
Resistance against shock		30g / 11 ms
Ambient temperature • during operating • during storage	°C	-25 ... +85 -40 ... +90
material / of the housing • of the switch head		metal
Design of the operating mechanism		metal lever, plastic roller
Minimum actuating force / in activation direction	N	10
Built in orientation		any
Item designation • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		E T

Certificates/approvals:

General Product Approval		Functional Safety / Safety of Machinery	Test Certificates
 CQC	 CSA	 VDE	 TÜV
ROSTEST		Manufacturer	
other			
Manufacturer			

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)
<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SE5000-0AE01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE5000-0AE01

last change:

Nov 28, 2011