







ACTUATOR HEAD FOR POSITION SWITCH 3SE51/52  
ANGULAR ROLLER LEVER METAL LEVER WITH PLASTIC  
ROLLER 13MM

### General technical details:

<b>product designation</b>		actuator head for position switch
<b>Mechanical operating cycles as operating time</b> • typical		15,000,000
<b>Resistance against vibration</b>		0.35 mm / 5g
<b>Resistance against shock</b>		30g / 11 ms
<b>Ambient temperature</b> • during operating • during storage	°C	-25 ... +85 -40 ... +90
<b>material / of the housing</b> • of the switch head		plastic
<b>Design of the operating mechanism</b>		metal lever, plastic roller
<b>Minimum actuating force / in activation direction</b>	N	10
<b>Built in orientation</b>		any
<b>Item designation</b> • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		E T

### Certificates/approvals:

General Product Approval		Functional Safety / Safety of Machinery	Test Certificates
 CQC	 CSA	 ROSTEST	 TÜV
 VDE		 Manufacturer	 Manufacturer
<b>other</b> <a href="#">Manufacturer</a>			

### Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**  
<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**  
<http://www.siemens.com/industrial-controls/mall>

---

**CAX-Online-Generator**

<http://www.siemens.com/cax>

---

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3SE5000-0AF10/all>

---

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3SE5000-0AF10](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE5000-0AF10)

---

**last change:**

Nov 28, 2011