



AS-INTERFACE ADAPTER ELEMENT WITH EXTERNAL  
AUXILIARY VOLTAGE FOR 4 SIGNALLING ELEMENTS  
BLACK DC 24 V

### General technical details:

<b>Product brand name</b>		SIRIUS
<b>product designation</b>		accessories for signaling columns, connection element for AS-Interface
<b>Type of voltage</b> • of the operating voltage		DC
<b>Operating voltage</b> • 1 / for DC / rated value	V	24
<b>Consumed current / for rated value of supply voltage</b>	mA	50
<b>Item designation</b> • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		E X

### Mechanical design:



<b>Color / of the housing</b>		miscellaneous
<b>External diameter / of the signal column element</b>	mm	50

### Ambient conditions:

<b>Ambient temperature</b> • during operating	°C	-20 ... +50
--	----	-------------

Protection class IP		IP54
Design of the interface / AS interface protocol		Yes
Depth	mm	50
Height	mm	55
Width	mm	50

#### Certificates/approvals:

General Product Approval	Shipping Approval	other
<a href="#">ROSTEST</a> 		<a href="#">Manufacturer</a> <a href="#">other</a>

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

##### Cax online generator:

<http://www.siemens.com/cax>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WD4228-0BB/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WD4228-0BB](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD4228-0BB)

last change:

Nov 4, 2011