

AS-INTERFACE SHAPED CABLE FOR EXT. AUX.
VOLTAGE 24V DC "BLACK,
TPE,
OIL-RESISTANT" SPECIAL DES. TO UL CLASS 2 2 X 1.5
QMM,
100M 1 PC. = 100 M



General technical data:

Design of the product		AS-Interface shaped cables
Colour		black (DC 24 V)
Material		TPE special version according to UL Class 2
Quantity		100 m roll

Mechanical design:

Without silicone precipitation		yes
bending radius / according to DIN VDE 0298 Part 300		
• fixed / min	m	12
• freely movable / min	m	24
Without halogens		no
Flexibility		good
Bending behavior according / according to DIN VDE 0472 Part 603		no break after 30000 reverse bending cycles
Core colours		brown, blue

Ambient conditions:

Fire behavior		flame-retardant according to IEC 60332-1; VDE 0482 T. 265-2-1; UL 1581 sec. 1061 cable flame; UL 1685 CSA FT4
resistance to oil		resistant

Ozone / and weather resistant		resistant
Temperature range		
• stationary		
• min	°C	-30
• max	°C	90
• moved		
• min	°C	-20
• max	°C	90

Certificates/approvals:

Approvals / Canada	CSA		C22.2 No. 214-02
Approvals / USA	UL		UL 758 AWM; UL 13 Class 2; UL 444 CMG
Monitored expertise (VDE)			no
General Product Approval	Shipping Approval	other	



[Declaration of Conformity](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RX9027-0AA00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RX9027-0AA00

last change:

Jul 1, 2013