



CIRCUIT-BREAKER SIZE S00,  
FOR MOTOR PROTECTION, CLASS 10,  
A-REL.0.45...0.63A,N-REL.8.2A SCREW TERMINAL,  
STANDARD SWITCHING CAPACITY

### General technical data:

Product brand name		SIRIUS
product designation		circuit breaker
Size of the circuit-breaker		S00
Trip class		CLASS 10
Degree of pollution		3
Installation altitude / at a height over sea level / maximum	m	2,000
Protection class IP / on the front		IP20
Ambient temperature		
• during storage	°C	-50 ... +80
• during operating	°C	-20 ... +70
• during transport	°C	80 ... -50
Resistance against shock		25g / 11 ms
Insulation voltage / rated value	V	690
Impulse voltage resistance / rated value	V	6,000
Active power loss / total / typical	W	5
Item designation		
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		Q
• according to DIN EN 61346-2		Q

<b>Mechanical operating cycles as operating time / of the main contacts / typical</b>		100,000
<b>Type of the driving mechanism / motor drive</b>		No
<b>Design of the operating mechanism</b>		rocker
<b>Product function</b>		
• overload protection		Yes
• phase disturbance recognition		Yes
<b>Product component</b>		
• auxiliary switch		No
• undervoltage release mechanism		No
• trip indicator		No
<b>Product extension / optional / motor drive</b>		No

<b>Main circuit:</b>		
<b>Number of poles / for main current circuit</b>		3
<b>type of voltage</b>		AC/DC
<b>Operating voltage / at AC-3 / rated value / maximum</b>	V	690
<b>Operating current / at AC-3 / at 400 V / rated value</b>	A	0.63
<b>Service power / at AC-3</b>		
• at 400 V / rated value	kW	0.18
<b>Frequency of operation / at AC-3 / according to IEC 60947-6-2 / maximum</b>	1/h	15
<b>Arrangement of electrical connectors / for main current circuit</b>		front side
<b>Adjustable response current</b>		
• of the non-delayed short-circuit release	A	8.2 ... 8.2
<b>Adjustable response current</b>		
• of the current-dependent overload release	A	0.45 ... 0.63
<b>Continuous current / rated value</b>	A	0.63
<b>Product extension / auxiliary switch</b>		Yes

<b>Auxiliary circuit:</b>		
<b>Number of NC contacts / for auxiliary contacts / instantaneous switching</b>		0
<b>Number of NO contacts / for auxiliary contacts / instantaneous switching</b>		0
<b>Number of change-over switches / for auxiliary contacts</b>		0

<b>Inputs/ Outputs:</b>		
<b>Number of digital inputs</b>		0












<b>Short-circuit:</b>		
<b>Breaking capacity limit short-circuit current (Icu)</b>		
• at 400 V / rated value	kA	100




• at 500 V / rated value	kA	100
• at 690 V / rated value	kA	100
<b>Design of the electrical connection / for auxiliary and control current circuit</b>		screw-type terminals
<b>Design of the overcurrent release and short-circuit release</b>		thermomagnetic

Installation/mounting/dimensions:		
<b>Built in orientation</b>		any
<b>Type of mounting</b>		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
<b>Width</b>	mm	45
<b>Height</b>	mm	90
<b>Depth</b>	mm	81
<b>Distance, to be maintained, to the ranks assembly</b>		
• backwards	mm	0
• sideways	mm	0
<b>Product function / removable terminal for auxiliary and control circuit</b>		No

Connections:		
<b>Design of the electrical connection</b>		screw-type terminals
• for main current circuit		
<b>Type of the connectable conductor cross-section</b>		
• for main contacts		
• solid		2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )
• stranded		2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )
• finely stranded		
• with conductor end processing		2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )
• for AWG conductors / for main contacts		2x (18 ... 14)
<b>Conductor cross section that can be connected / for main contacts</b>		
• solid	mm <sup>2</sup>	0.5 ... 2.5
• stranded	mm <sup>2</sup>	0.5 ... 2.5
• stranded wire		
• with conductor end processing	mm <sup>2</sup>	0.5 ... 2.5
<b>AWG number / as coded connectable conductor cross-section</b>		
• for main contacts		18 ... 14

Certificates/approvals:		
-------------------------	--	--

General Product Approval					For use in hazardous locations
		<a href="#">KETI</a>	<a href="#">ROSTEST</a>		<a href="#">DEKRA EXAM, DMT</a>
CQC	CSA			UL	
Test Certificates					
<a href="#">Manufacturer</a>					
Shipping Approval					
					
ABS	BUREAU VERITAS	DNV	GL	LRS	PRS
Shipping Approval		other			
		<a href="#">Manufacturer</a>	<a href="#">other</a>		
RINA	RMRS				
Safety:					
Protection against electrical shock				finger-safe	
Further information:					
Information- and Downloadcenter (Catalogs, Brochures,...)					
<a href="http://www.siemens.com/industrial-controls/catalogs">http://www.siemens.com/industrial-controls/catalogs</a>					
Industry Mall (Online ordering system)					
<a href="http://www.siemens.com/industrial-controls/mall">http://www.siemens.com/industrial-controls/mall</a>					
CAx-Online-Generator					
<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>					
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)					
<a href="http://support.automation.siemens.com/WW/view/en/3RV1011-0GA10/all">http://support.automation.siemens.com/WW/view/en/3RV1011-0GA10/all</a>					
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)					
<a href="http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RV1011-0GA10">http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RV1011-0GA10</a>					



last change:

Dec 24, 2011