

Flashlight element, with integrated LED, yellow, 24 V AC/DC,
Diameter 50 mm



Figure similar

General technical data	
Product brand name	SIRIUS
Product designation	Repeated-flash light element
Design of the optical signal	blinklight
Type of voltage of the operating voltage	AC/DC
Operating voltage	
• 1 at DC rated value	24 V
• 1 at AC at 50 Hz rated value	24 V
• 1 at AC at 60 Hz rated value	24 V
Relative positive tolerance of the operating voltage	10 %
Relative negative tolerance of the operating voltage	-10 %
Consumed current maximum	35 mA
Service life of LED	100 000 h
Color	yellow
Mounting type	Bayonet
Reference code	
• acc. to DIN EN 61346-2	P

Mechanical data

Outer diameter of the signal column element	50 mm
---	-------

Lamp

Product component Light source	Yes
Type of light source	LED
Flash frequency	1 Hz
Light intensity	4.96 cd
Light intensity	2.99 ... 6.98 cd

Ambient conditions

Ambient temperature during operation	-20 ... +50 °C
Protection class IP	IP54
Height	67 mm
Width	52 mm

Certificates/approvals

General Product Approval

EMC

Declaration of
Conformity

other



UL



C-Tick



EG-Konf.

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WD4220-5BD>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD4220-5BD>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WD4220-5BD>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD4220-5BD&lang=en



last modified:



W9.4444; 8WD42..._ALL
W6.8611; 8WD42..._ALL
06/15/2018