

Differential current monitoring device Digital 4-channel, Type A IDN
0.03 A 30 A 0.02 10 sec. (INS, SEL)



Figure similar

Model	
Product brand name	SETRON
Product designation	Residual current monitor
Design of the product	Digital, type A
Type of voltage / of the operating voltage / for actuation	AC
Operating voltage • rated value / maximum	276 V
Main circuit	
Operating frequency / rated value • minimum • maximum	50 Hz 60 Hz
Auxiliary circuit	
Number of NC contacts / for auxiliary contacts	0
Number of NO contacts / for auxiliary contacts	5
Suitability	

Suitability for operation	For AC networks
---------------------------	-----------------

Product function

Product function / Fault storage	Yes
----------------------------------	-----

Connections

Type of electrical connection	screw-type terminals
-------------------------------	----------------------

Mechanical Design

Height	85 mm
Width	54 mm
Depth	68 mm
Net weight	272 g

Certificates

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



UR



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV8200-6KK>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SV8200-6KK>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV8200-6KK

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

