

RES.CUR.OP.CIRCUIT BREAKER TYPE A 80A 3+N-
POLE 300MA 400V 4MW N-LEFT



Model		
product brand name		SETRON
Product designation		RCCB
Design of the product		Instantaneous
Product variations		N left
General technical data		
Number of poles		4
Size of installation devices / acc. to DIN 43880		1
Protection against electrical shock		Finger and back-of-hand safe
Short-circuit current rating	kA	10
circuit-breaker / Design		5SV3
Mechanical service life (switching cycles) / typical		10 000
Overvoltage category		III
Supply voltage		
Supply voltage frequency		
• Rated value	Hz	50
Protection class		
Protection class IP		IP20, if the distribution board is installed, with connected conductors

Switching capacity		
Switching capacity current		
• acc. to EN 60898 / Rated value	kA	0.8
Electricity		
Tripping residual current / Rated value	mA	300
rated current I_n / IEC, DIN/VDE		
• at 40 Cel	A	80
Current / with AC		
• Rated value	A	80
Surge current resistance		
• Rated value	kA	1
Appearance		
Product details		
Product property		
• halogen-free		Yes
• silicon-free		Yes
Product expansion / can be installed		
• supplementary devices		Yes
Number		
Number of test cycles / for environmental testing / acc. to IEC 60068-2-30		28
Connections		
Connectable conductor cross-section / stranded		
• minimum	mm ²	0.75
• maximum	mm ²	35
Connectable conductor cross-section		
• solid		
— minimum	mm ²	0.75
— maximum	mm ²	35
Tightening torque / with screw-type terminals		
• minimum	N·m	2.5
• maximum	N·m	3
Position		
• of power supply cord		top or bottom
Mechanical Design		
Height	mm	90
Width	mm	72
Depth	mm	70
mounting position		any
Installation depth	mm	70
Number of width units		4

Mounting type

DIN rail (REG)

Environmental conditions

Ambient temperature

- minimum
- maximum
- during storage / minimum permissible
- during storage / maximum permissible

°C -25
°C 45
°C -40
°C 75

Certificates

Reference code

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

F
F

General Product Approval



[other](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb-automation.siemens.com/mall/en/WW/Catalog/Product/5SV36476KL>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SV36476KL/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV36476KL

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>



Siemens

5SV(3,4)x4x-x

Format / Size: Hybrid quer

last modified:

21.10.2014