

RES.CUR.OP.CIRCUIT BREAKER TYPE A 63A 3+N-  
POLE 300MA 400V 4MW SHORT-TIME DELAYED



| Model                                                |    |                              |
|------------------------------------------------------|----|------------------------------|
| product brand name                                   |    | SENTRON                      |
| Product designation                                  |    | RCCB                         |
| Design of the product                                |    | Short-time delayed           |
| General technical data                               |    |                              |
| Number of poles                                      |    | 4                            |
| Size of installation devices / acc. to DIN 43880     |    | 1                            |
| Protection against electrical shock                  |    | Finger and back-of-hand safe |
| Short-circuit current rating                         | kA | 10                           |
| circuit-breaker / Design                             |    | 5SV3                         |
| Mechanical service life (switching cycles) / typical |    | 10 000                       |
| Overvoltage category                                 |    | III                          |
| Supply voltage                                       |    |                              |
| Supply voltage                                       |    |                              |
| • at AC / Rated value                                | V  | 400                          |
| • for testing equipment / minimum                    | V  | 100                          |
| Protection class                                     |    |                              |

|                                                                                   |                 |                                                                         |
|-----------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------|
| <b>Protection class IP</b>                                                        |                 | IP20, if the distribution board is installed, with connected conductors |
| <b>Switching capacity</b>                                                         |                 |                                                                         |
| <b>Switching capacity current</b>                                                 |                 |                                                                         |
| • acc. to EN 60898 / Rated value                                                  | kA              | 0.8                                                                     |
| <b>Dissipation</b>                                                                |                 |                                                                         |
| <b>Active power loss</b>                                                          |                 |                                                                         |
| • for rated value of the current / at AC / in hot operating state / per pole      | W               | 3.9                                                                     |
| <b>Electricity</b>                                                                |                 |                                                                         |
| <b>Tripping residual current / Rated value</b>                                    | mA              | 300                                                                     |
| rated current I <sub>n</sub> / IEC, DIN/VDE / at 40 °C                            | A               | 63                                                                      |
| <b>Type of fault current</b>                                                      |                 | A                                                                       |
| Current / at AC / Rated value                                                     | A               | 63                                                                      |
| Surge current resistance / Rated value                                            | kA              | 3                                                                       |
| <b>Product details</b>                                                            |                 |                                                                         |
| <b>Product property</b>                                                           |                 |                                                                         |
| • halogen-free                                                                    |                 | Yes                                                                     |
| • silicon-free                                                                    |                 | Yes                                                                     |
| Product expansion / can be installed / supplementary devices                      |                 | Yes                                                                     |
| <b>Number</b>                                                                     |                 |                                                                         |
| <b>Number of test cycles / for environmental testing / acc. to IEC 60068-2-30</b> |                 | 28                                                                      |
| <b>Connections</b>                                                                |                 |                                                                         |
| <b>Connectable conductor cross-section / stranded</b>                             |                 |                                                                         |
| • minimum                                                                         | mm <sup>2</sup> | 0.75                                                                    |
| • maximum                                                                         | mm <sup>2</sup> | 35                                                                      |
| <b>Connectable conductor cross-section / solid</b>                                |                 |                                                                         |
| • minimum                                                                         | mm <sup>2</sup> | 0.75                                                                    |
| • maximum                                                                         | mm <sup>2</sup> | 35                                                                      |
| <b>Tightening torque / with screw-type terminals</b>                              |                 |                                                                         |
| • minimum                                                                         | N·m             | 2.5                                                                     |
| • maximum                                                                         | N·m             | 3                                                                       |
| Position / of power supply cord                                                   |                 | top or bottom                                                           |
| <b>Mechanical Design</b>                                                          |                 |                                                                         |
| <b>Height</b>                                                                     | mm              | 90                                                                      |
| <b>Width</b>                                                                      | mm              | 72                                                                      |
| <b>Depth</b>                                                                      | mm              | 70                                                                      |
| <b>mounting position</b>                                                          |                 | any                                                                     |

|                       |    |                |
|-----------------------|----|----------------|
| Installation depth    | mm | 70             |
| Number of width units |    | 4              |
| Mounting type         |    | DIN rail (REG) |

#### Environmental conditions

##### Ambient temperature

|                                        |    |     |
|----------------------------------------|----|-----|
| • minimum                              | °C | -25 |
| • maximum                              | °C | 45  |
| • during storage / minimum permissible | °C | -40 |
| • during storage / maximum permissible | °C | 75  |

#### Certificates

##### Equipment marking

|                          |   |
|--------------------------|---|
| • acc. to DIN EN 61346-2 | F |
| • acc. to DIN EN 81346-2 | F |

#### General Product Approval

#### Declaration of Conformity



#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SV36466KK01>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SV36466KK01/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SV36466KK01](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV36466KK01)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>



last modified:

22.09.2015