

Number of poles

3



FUSE-SWITCH-DISCONNECTOR 3-POLE, NH2,
400A 60MM BUSBAR SYSTEM COVER LEVEL 32/70 MM
FLAT CONNECTOR

Similar to image

General technical details:

product brand name	SENTRON
Product designation	Fuse switch disconnecter
Fuse system	LV HRC fuse
Installation size of fuse-link	NH1. NH2
Installation size of disconnecting link	2 and 1
Type from device	Zum Aufschrauben auf Sammelschienensystem Siemens 8US 60 mm
Design of the product	3-pole
Busbar design	Sammelschienendicke 5 oder 10 mm
Design of the operating mechanism	handle unit
Type of the driving mechanism / motor drive	No
Number of NC contacts / for auxiliary contacts	0
Number of NO contacts / for auxiliary contacts	0
Number of changeover contacts / for auxiliary contacts	0
Design of the load switch / Strip form	No
Product equipment / interlock	Yes
Product feature / sealable	Yes

Product component <ul style="list-style-type: none">• phase failure monitoring• undervoltage release mechanism• undervoltage release with leading contact• trip indicator		No
		No
		No
		No
Acceptability for application <ul style="list-style-type: none">• switch disconnecter• emergency stop switch• main switch• safety cut-out switch• maintenance/repair switch		Yes
		No
		No
		Yes
		Yes
Product function <ul style="list-style-type: none">• fuse monitoring• overvoltage protection monitoring		No
		No
Product extension <ul style="list-style-type: none">• auxiliary switch• optional<ul style="list-style-type: none">• fuse monitoring• phase failure monitoring• voltage trigger• overvoltage protection monitoring• locking capability• motor drive		Yes
		Yes
		Yes
		No
		Yes
		Yes
		No
		No
Continuous current <ul style="list-style-type: none">• rated value• at 35 °C / rated value• at 40 °C / rated value• at 45 °C / rated value• at 50 °C / rated value• at 55 °C / rated value	A	400
	A	400
	A	400
	A	392
	A	372
	A	356
Operating current <ul style="list-style-type: none">• at AC-21 B<ul style="list-style-type: none">• at 400 V / rated value• at 500 V / rated value• at 690 V / rated value• at AC-22 B<ul style="list-style-type: none">• at 400 V / rated value• at 500 V / rated value• at 690 V / rated value• at AC-23 B	A	400
	A	400
	A	400
	A	400
	A	400
	A	400
	A	400
	A	400
	A	400

• at 400 V / rated value	A	400
• at 500 V / rated value	A	315
• at 690 V / rated value	A	125
• at DC-21 B		
• at 240 V / rated value / maximum	A	400
• at 440 V / rated value / maximum	A	400
• at DC-22 B		
• at 240 V / rated value / maximum	A	400
• at 440 V / rated value / maximum	A	315
• at DC-23 B		
• at 240 V / rated value / maximum	A	250
• at 440 V / rated value / maximum	A	160
• with capacitive load		
• at 400 V / maximum	A	72
• at 500 V / maximum	A	55
Let-through current		
• with speedy activation / maximum permissible	kA	40
• with closed switch / maximum permissible	kA	40
Conditional short-circuit current (I_q)		
• rated value	kA	80
• at 500 V / with AC / with speedy activation / rated value	kA	80
• at 690 V / with AC / with speedy activation / rated value	kA	50
• with closed switch		
• at 500 V / with AC / rated value	kA	100
• at 690 V / with AC / rated value	kA	100
Operating voltage / for DC / rated value		
	V	440
Tension d'emploi		
• for AC / rated value	/ V	690
• for DC / rated value		
• maximum	V	440
Power factor		
• at AC-21 B		0.95
• at AC-22 B		0.65
• at AC-23 B		0.35
• with capacitive load		-0.25
Active power loss / maximum		
	W	34
Insulation voltage / rated value		
	V	690
Impulse voltage resistance / rated value		
	kV	8
I²t value / with closed switch / maximum permissible		
	kA ² ·s	2,150
Item designation		

- according to DIN EN 61346-2
- according to DIN EN 81346-2

Q
Q

Connection elements and terminals:

Design of the electrical connection / for main current circuit

flat connector

Conductor cross section that can be connected / for main contacts

- single- or multi-stranded
- stranded

mm²

25 ... 240

mm²

25 ... 240

Tightening torque

- with screw-type terminals

N·m

10 ... 12

Arrangement of electrical connectors / for main current circuit

sonstige

Degree of protection and safety class:

IP degree of protection

- open
- on the front
- with closed switch
 - without cover or cable lug cover
 - with cover or cable lug cover

IP20

IP40

IP30

IP40

Degree of pollution

3

Mechanical operating cycles as operating time / typical

1,000

Ambient conditions:

Ambient temperature

- during operating
- during storage

°C

-25 ... +55

°C

-50 ... +80

Installation/mounting/dimensions:

Mounting type

- rail mounting
- front mounting
- front mounting with central attachment
- front mounting with 4-hole attachment
- floor mounting

busbar mounting

Yes

No

No

No

No

mounting position

waagerecht oder senkrecht

Width

mm

209.4

Height

mm

306

Depth

mm

155.9

Largeur

- du jeu de barres

mm

12 ... 30

Center line spacing

mm

60

Net weight

kg

4.76

Certificates/approvals:

General Product Approval



CCC



GOST



UL



UR



EG-Konf.

Test Certificates

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



DNV

Shipping Approval



GL



LRS

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NP1153-1BC10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NP1153-1BC10/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NP1153-1BC10


CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)





last change:

Mar 31, 2014