

REV. COMB., AC3, 5.5KW/ 400V AC230V,  
50/60HZ, 3-POLE,  
SZ S00 SCREW TERMINAL ELECTR. AND MECH.  
INTERLOCK



### General technical data:

|  |    |                                    |
|--|----|------------------------------------|
| Product brand name   |    | SIRIUS                             |
| product designation  |    | reversing contactor assembly 3RA23 |
| Product function   |    | reversing contactor                |
| Size of the contactor  |    | S00                                |
| Protection class IP / on the front   |    | IP20                               |
| Degree of pollution  |    | 3                                  |
| Insulation voltage / with degree of pollution 3 / rated value  | V  | 690                                |
| Installation altitude / at a height over sea level / maximum   | m  | 2,000                              |
| Ambient temperature <ul style="list-style-type: none"> <li>during transport</li> <li>during storage</li> <li>during operating</li> </ul>   | °C | -55 ... 80                         |
|  | °C | -55 ... 80                         |
|  | °C | -25 ... 60                         |
| Resistance against shock   |    | 9.8g / 5 ms and 5.9g / 10 ms       |
| Impulse voltage resistance / rated value   | kV | 6                                  |
| Active power loss / per conductor / typical  | W  | 1.2                                |
| Item designation <ul style="list-style-type: none"> <li>according to DIN 40719 extendable after IEC 204-2 / according to IEC 750</li> <li>according to DIN EN 61346-2</li> </ul> |    | K                                  |
|  |    | Q                                  |

|  |  |                               |
|--|--|-------------------------------|
| <b>Manufacturer article number</b>                             |  |                               |
| • 1 / of the contactor included in the scope of supply         |  | <a href="#">3RT2017-1AP02</a> |
| • 2 / of the contactor included in the scope of supply         |  | <a href="#">3RT2017-1AP02</a> |
| • of the RS applied assembly kit                               |  | <a href="#">3RA2913-2AA1</a>  |
| <b>Mechanical operating cycles as operating time</b>           |  |                               |
| • of the main contacts / typical                               |  | 10,000,000                    |
| • of the auxiliary contacts / typical                          |  | 10,000,000                    |
| • of the contactor / typical                                   |  | 10,000,000                    |
| • of the contactor with added auxiliary switch block / typical |  | 10,000,000                    |

#### Communication:

|   |  |    |
|---|--|----|
| <b>Product function</b>                                     |  |    |
| • bus-communication   |  | No |
| • control circuit interface with IO link                    |  | No |
| <b>Protocol / will be supported / AS interface protocol</b> |  | No |

#### Main circuit:

|  |   |      |
|--|---|------|
| <b>Number of poles / for main current circuit</b>          |   | 3    |
| <b>Number of NC contacts / for main contacts</b>           |   | 0    |
| <b>Number of NO contacts / for main contacts</b>           |   | 3    |
| <b>Operating voltage / at AC-3 / rated value / maximum</b> | V | 690  |
| <b>Operating current</b>                                   |   |      |
| • at AC-1 / at 400 V                                       |   |      |
| • at 40 °C ambient temperature / rated value               | A | 18   |
| • at 60 °C ambient temperature / rated value               | A | 16   |
| • at AC-2 / at 400 V / rated value                         | A | 7    |
| • at AC-3 / at 400 V / rated value                         | A | 12   |
| • at AC-4 / at 400 V / rated value                         | A | 6.5  |
| • with 1 current path / at DC-1                            |   |      |
| • at 24 V / rated value                                    | A | 20   |
| • at 110 V / rated value                                   | A | 2.1  |
| • with 2 current paths in series / at DC-1                 |   |      |
| • at 24 V / rated value                                    | A | 20   |
| • at 110 V / rated value                                   | A | 12   |
| • with 3 current paths in series / at DC-1                 |   |      |
| • at 24 V / rated value                                    | A | 20   |
| • at 110 V / rated value                                   | A | 20   |
| • with 1 current path / at DC-3 / at DC-5                  |   |      |
| • at 24 V / rated value                                    | A | 20   |
| • at 110 V / rated value                                   | A | 0.15 |

|  |     |       |
|--|-----|-------|
| <ul style="list-style-type: none"> <li>• with 2 current paths in series / at DC-3 / at DC-5 <ul style="list-style-type: none"> <li>• at 24 V / rated value</li> <li>• at 110 V / rated value</li> </ul> </li> <li>• with 3 current paths in series / at DC-3 / at DC-5 <ul style="list-style-type: none"> <li>• at 24 V / rated value</li> <li>• at 110 V / rated value</li> </ul> </li> </ul> | A   | 20    |
|  | A   | 0.35  |
|  | A   | 20    |
|  | A   | 20    |
| <b>Service power</b>   |     |       |
| <ul style="list-style-type: none"> <li>• at AC-2 / at 400 V / rated value</li> </ul>   | kW  | 5.5   |
| <ul style="list-style-type: none"> <li>• at AC-3 <ul style="list-style-type: none"> <li>• at 400 V / rated value</li> <li>• at 500 V / rated value</li> <li>• at 690 V / rated value</li> </ul> </li> <li>• at AC-4 / at 400 V / rated value</li> </ul>  | kW  | 5.5   |
|  | kW  | 5.5   |
|  | kW  | 5.5   |
|  | kW  | 2     |
| <b>Off-load operating frequency</b>  | 1/h | 15    |
| <b>Frequency of operation</b>  |     |       |
| <ul style="list-style-type: none"> <li>• at AC-1 / according to IEC 60947-6-2 / maximum</li> </ul>   | 1/h | 1,000 |
| <ul style="list-style-type: none"> <li>• at AC-2 / according to IEC 60947-6-2 / maximum</li> </ul>   | 1/h | 750   |
| <ul style="list-style-type: none"> <li>• at AC-3 / according to IEC 60947-6-2 / maximum</li> </ul>   | 1/h | 750   |
| <ul style="list-style-type: none"> <li>• at AC-4 / according to IEC 60947-6-2 / maximum</li> </ul>   | 1/h | 250   |

|  |     |              |
|--|-----|--------------|
| <b>Control circuit:</b>  |     |              |
| <b>Design of activation</b>  |     | conventional |
| <b>Type of voltage / of the controlled supply voltage</b>                              |     | AC           |
| <b>Control supply voltage frequency</b>  |     |              |
| <ul style="list-style-type: none"> <li>• 1 / rated value</li> </ul>                    | Hz  | 50           |
| <ul style="list-style-type: none"> <li>• 2 / rated value</li> </ul>                    | Hz  | 60           |
| <b>Control supply voltage / 1</b>  |     |              |
| <ul style="list-style-type: none"> <li>• at 50 Hz / for AC / rated value</li> </ul>    | V   | 230          |
| <ul style="list-style-type: none"> <li>• at 60 Hz / for AC / rated value</li> </ul>    | V   | 230          |
| <b>Operating range factor control supply voltage rated value / of the solenoid</b>     |     |              |
| <ul style="list-style-type: none"> <li>• at 50 Hz / for AC</li> </ul>                  |     | 0.8 ... 1.1  |
| <ul style="list-style-type: none"> <li>• at 60 Hz / for AC</li> </ul>                  |     | 0.85 ... 1.1 |
| <b>Apparent pull-in power / of the solenoid / for AC</b>                               | V·A | 37           |
| <b>Apparent holding power / of the solenoid / for AC</b>                               | V·A | 5.7          |
| <b>Inductive power factor</b>  |     |              |
| <ul style="list-style-type: none"> <li>• with the pull-in power of the coil</li> </ul> |     | 0.8          |
| <ul style="list-style-type: none"> <li>• with the pull-in power of the coil</li> </ul> |     | 0.28         |
| <b>Auxiliary circuit:</b>  |     |              |
| <b>Product extension / auxiliary switch</b>  |     | Yes          |

|  |   |  |
|--|---|--|
| <b>Contact reliability / of the auxiliary contacts</b> |   | < 1 error per 100 million operating cycles |
| <b>Number of NC contacts / for auxiliary contacts</b>  |   |  |
| • per direction of rotation                            |   | 0  |
| • instantaneous switching                              |   | 0  |
| • lagging switching                                    |   | 0  |
| <b>Number of NO contacts / for auxiliary contacts</b>  |   |  |
| • per direction of rotation                            |   | 0  |
| • instantaneous switching                              |   | 0  |
| • leading switching                                    |   | 0  |
| <b>Operating current / of the auxiliary contacts</b>   |   |  |
| • at AC-12 / maximum                                   | A | 10   |
| • at AC-15   |   |  |
| • at 230 V   | A | 6  |
| • at 400 V   | A | 3  |
| • at DC-12   |   |  |
| • at 48 V  | A | 6  |
| • at 60 V  | A | 6  |
| • at 110 V   | A | 3  |
| • at 220 V   | A | 1  |
| • at DC-13   |   |  |
| • at 24 V  | A | 10   |
| • at 48 V  | A | 2  |
| • at 60 V  | A | 2  |
| • at 110 V   | A | 1  |
| • at 220 V   | A | 0.3  |

#### Short-circuit:

##### Design of the fuse link

- for short-circuit protection of the main circuit
- with type of assignment 1 / required
- at type of coordination 2 / required
- for short-circuit protection of the auxiliary switch / required

gL/gG LV HRC 3NA, DIAZED 5SB, NEOZED 5SE: 35 A  
gL/gG LV HRC 3NA, DIAZED 5SB, NEOZED 5SE: 20 A  
fuse gL/gG: 10 A

#### Installation/mounting/dimensions:

|                             |    |  |
|-----------------------------|----|--|
| <b>Built in orientation</b> |    | any  |
| <b>Type of mounting</b>     |    | screw and snap-on mounting onto 35 mm standard mounting rail |
| <b>Width</b>                | mm | 90   |
| <b>Height</b>               | mm | 68   |
| <b>Depth</b>                | mm | 73   |

|  |    |   |
|--|----|---|
| <b>Distance, to be maintained, to the ranks assembly</b> |    |   |
| • forwards   | mm | 6 |
| • backwards  | mm | 0 |
| • upwards  | mm | 6 |
| • downwards  | mm | 6 |
| • sideways   | mm | 6 |
| <b>Distance, to be maintained, to earthed part</b>       |    |   |
| • forwards   | mm | 6 |
| • backwards  | mm | 0 |
| • upwards  | mm | 6 |
| • downwards  | mm | 6 |
| • sideways   | mm | 6 |
| <b>Distance, to be maintained, conductive elements</b>   |    |   |
| • forwards   | mm | 6 |
| • backwards  | mm | 0 |
| • upwards  | mm | 6 |
| • downwards  | mm | 6 |
| • sideways   | mm | 6 |

#### Connections:

|  |  |   |
|--|--|---|
| <b>Design of the electrical connection</b>             |  |   |
| • for main current circuit                             |  | screw-type terminals  |
| • for auxiliary and control current circuit            |  | screw-type terminals  |
| <b>Type of the connectable conductor cross-section</b> |  |   |
| • for main contacts                                    |  |   |
| • solid  |  | 2 x (0.5 ... 1.5 mm <sup>2</sup> ), 2 x (0.75 ... 2.5 mm <sup>2</sup> ), 2 x (0.5 ... 4 mm <sup>2</sup> ) |
| • stranded   |  | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 4 mm <sup>2</sup> )    |
| • finely stranded                                      |  |   |
| • with conductor end processing                        |  | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )                                     |
| • for AWG conductors / for main contacts               |  | 2x (20 ... 16), 2x (18 ... 14)  |
| • for auxiliary contacts                               |  |   |
| • solid  |  | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )                                     |
| • finely stranded                                      |  |   |
| • with conductor end processing                        |  | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )                                     |
| • for AWG conductors / for auxiliary contacts          |  | 2x (20 ... 16), 2x (18 ... 14)  |

#### Certificates/approvals:

|                                    |  |                     |
|------------------------------------|--|---------------------|
| <b>Verification of suitability</b> |  | CE / UL / CSA / CCC |
|------------------------------------|--|---------------------|

## General Product Approval



[ROSTEST](#)



## Test Certificates

[Manufacturer](#)

## Shipping Approval



GL



LRS



PRS



RINA

## Shipping Approval

other



[other](#)

## UL/CSA ratings

### yielded mechanical performance (hp)

- for single-phase squirrel cage motors
  - at 110/120 V / rated value
  - at 230 V / rated value
- for three-phase squirrel cage motors
  - at 200/208 V / rated value
  - at 220/230 V / rated value
  - at 460/480 V / rated value
  - at 575/600 V / rated value

|    |     |
|----|-----|
| hp | 0.5 |
| hp | 2   |
| hp | 1.5 |
| hp | 3   |
| hp | 7.5 |
| hp | 10  |

### Operating current (FLA) / for three-phase squirrel cage motors

- at 480 V / rated value
- at 600 V / rated value

|   |    |
|---|----|
| A | 11 |
| A | 11 |

### Contact rating designation / for auxiliary contacts / according to UL

A600 / Q600

## Safety:

### B10 value / with high demand rate

- according to SN 31920

1,000,000

### Failure rate (FIT value) / with low demand rate

- according to SN 31920

FIT 100

### Proportion of dangerous failures

- with low demand rate / according to SN 31920
- with high demand rate / according to SN 31920

|   |    |
|---|----|
| % | 40 |
| % | 75 |

### T1 value / for proof test interval or service life

- according to IEC 61508

a 20

### Protection against electrical shock

finger-safe

## Further information:

---

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

---

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

---

**CAX-Online-Generator**

<http://www.siemens.com/cax>

---

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**




<http://support.automation.siemens.com/WW/view/en/3RA2317-8XB30-1AP0/all>

---

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3RA2317-8XB30-1AP0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RA2317-8XB30-1AP0)

---



last change:

Oct 24, 2011