

LOAD FEEDER FUSELESS REVERSING DUTY,  
AC 400V, SZ S0, 14. . .20A,  
DC 24V SCREW TERMINAL FOR RAIL-MOUNTING,  
W. DIN RAIL ADAPTER TYPE OF COORDINATION 1,  
IQ = 150KA 1NO+1NC (CONTACTOR)

### General technical data:

Product brand name		SIRIUS
product designation		non-fused load feeders 3RA2
Design of the product		reversing starter
Size of the load feeder		S0
Protection class IP / on the front		IP20
Degree of pollution		3
Insulation voltage / rated value	V	690
Installation altitude / at a height over sea level / maximum	m	2,000
Ambient temperature <ul style="list-style-type: none"> <li>during transport</li> <li>during storage</li> <li>during operating</li> </ul>	°C	-55 ... 80 -55 ... 80 -20 ... 60
Impulse voltage resistance / rated value	kV	6
Active power loss / per conductor / typical	W	4.3
Item designation <ul style="list-style-type: none"> <li>according to DIN 40719 extendable after IEC 204-2 / according to IEC 750</li> <li>according to DIN EN 61346-2</li> </ul>		Q Q
Type of assignment		2

<b>Mechanical operating cycles as operating time / of the contactor</b>		
• typical		10,000,000
<b>Manufacturer article number</b>		
• of the standard mounting rail adapter included in the scope of supply		<a href="#">3RA2922-1AA00</a>
• of the circuit-breakers included in the scope of supply		<a href="#">3RV2021-4BA10</a>
• of the contactor included in the scope of supply		<a href="#">3RT2026-1BB40</a>
• of the link module included in the scope of supply		<a href="#">3RA2921-1BA00</a>
• of the RH applied assembly kit		<a href="#">3RA2923-1BB1</a>
<b>Design of the switching contact</b>		mechanical
<b>Type of the motor protection</b>		bimetal
<b>Adjustable response current</b>		
• of the current-dependent overload release	A	14 ... 20

#### Communication:

<b>Product function / bus-communication</b>		No
<b>Protocol / will be supported</b>		
• AS interface protocol		No
• PROFIBUS DP protocol		No
• PROFINET protocol		No
<b>Product extension / function module for communication</b>		No

#### Main circuit:

<b>Number of poles / for main current circuit</b>		3
<b>Number of NC contacts / for main contacts</b>		0
<b>Number of NO contacts / for main contacts</b>		3
<b>Operating voltage / at AC-3 / rated value / maximum</b>	V	690
<b>Operating current</b>		
• at AC-1 / at 400 V / rated value	A	20
• at AC-2 / at 400 V / rated value	A	15.5
• at AC-3 / at 400 V / rated value	A	15.5
• at AC-4 / at 400 V / rated value	A	15.5
<b>Service power</b>		
• at AC-2 / at 400 V / rated value	W	7,500
• at AC-3		
• at 400 V / rated value	W	7,500
• at 500 V / rated value	W	11,000
• at 690 V / rated value	W	15,000
• at AC-4 / at 400 V / rated value	W	7,500
<b>Off-load operating frequency</b>	1/h	1,500
<b>Frequency of operation</b>		

- at AC-1 / according to IEC 60947-6-2 / maximum
- at AC-2 / according to IEC 60947-6-2 / maximum
- at AC-3 / according to IEC 60947-6-2 / maximum
- at AC-4 / according to IEC 60947-6-2 / maximum

1/h	1,000
1/h	1,000
1/h	1,000
1/h	300

#### Control circuit:

Type of voltage / of the controlled supply voltage		DC
Control supply voltage frequency		
• 1 / rated value	Hz	0
Control supply voltage / 1		
• for DC / rated value	V	24
Holding power / of the solenoid / for DC	W	5.9

#### Auxiliary circuit:

Product extension / auxiliary switch		Yes
Number of NC contacts / for auxiliary contacts		1
Number of NO contacts / for auxiliary contacts		1
Number of change-over switches / for auxiliary contacts		0

#### Inputs/ Outputs:

Number of digital inputs		0
--------------------------	--	---

#### Short-circuit:

Product function / short circuit protection		Yes
Design of the short-circuit protection		circuit-breakers
Breaking capacity limit short-circuit current (Icu)		
• at 400 V / rated value	A	25,000
• at 500 V / rated value	A	5,000
• at 690 V / rated value	A	2,000

#### Installation/mounting/dimensions:

Built in orientation		vertical
Type of mounting		screw and snap-on mounting onto 35 mm standard mounting rail
Width	mm	90
Height	mm	265
Depth	mm	129.9
Distance, to be maintained, to the ranks assembly		
• forwards	mm	10
• backwards	mm	0
• upwards	mm	30
• downwards	mm	30

• sideways	mm	0
<b>Distance, to be maintained, to earthed part</b>		
• forwards	mm	10
• backwards	mm	0
• upwards	mm	30
• downwards	mm	10
• sideways	mm	9
<b>Distance, to be maintained, conductive elements</b>		
• forwards	mm	10
• backwards	mm	0
• upwards	mm	30
• downwards	mm	10
• sideways	mm	9

### Connections:

<b>Design of the electrical connection</b>		
• for main current circuit		screw-type terminals
• for auxiliary and control current circuit		screw-type terminals
<b>Type of the connectable conductor cross-section</b>		
• for main contacts		
• solid		2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 10 mm <sup>2</sup> )
• stranded		2x (1.0 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 10 mm <sup>2</sup> )
• finely stranded		
• with conductor end processing		2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> ), 1x 10 mm <sup>2</sup>
• for AWG conductors / for main contacts		2 x (16 ... 14), 2x (14 ... 8)
• for auxiliary contacts		
• solid		2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )
• finely stranded		
• with conductor end processing		2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )
• for AWG conductors / for auxiliary contacts		2x (20 ... 14)

### Certificates/approvals:

<b>Verification of suitability</b>		CE / UL / CSA / CCC
<b>Varification of suitability / ATEX</b>		No

<b>General Product Approval</b>	<b>For use in hazardous locations</b>	<b>Test Certificates</b>
---------------------------------	---------------------------------------	--------------------------

[ROSTEST](#)



[DEKRA EXAM,](#)  
[DMT](#)

[Manufacturer](#)

**Shipping Approval**

**other**



ABS



PRS



RINA

[Manufacturer](#)

[other](#)

## Safety:

### B10 value / with high demand rate

- according to SN 31920

1,000,000

### Failure rate (FIT value) / with low demand rate

- according to SN 31920

FIT

250

### Proportion of dangerous failures

- with low demand rate / according to SN 31920
- with high demand rate / according to SN 31920

%

40

%

75

### T1 value / for proof test interval or service life

- according to IEC 61508

a

10

### Protection against electrical shock

finger-safe

## Further information:

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

### CAX-Online-Generator



<http://www.siemens.com/cax>


### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RA2220-4BB26-0BB4/all>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3RA2220-4BB26-0BB4](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RA2220-4BB26-0BB4)





last change:

Oct 24, 2011